

Clay District, Monongalia County, W. Va.  
By Valley Steel Products Co., St. Louis, Mo.  
Abandoned under permit Mon-.....-A1  
On 77.608 acres, on Dolls Run.  
Elevation, 1372' L.

Date of completion, etc., not given.

10" casing, 744' (pulled); 8 1/2", 1610'; 6 3/4", 1760'; 4-7/8", 2012';  
2" tubing, 2128'.

Oil well. Record to Dept. of Mines stamped Sept. 8, 1951.

Record to RCT from Mrs. Griffith Feb. 29, 1952. Old File No. 570.

	Top.	Bottom.
Pittsburgh Coal	716	.....
(Light flow of gas at 2005')		
(More gas, 2088')		
(First pay oil at 2094')		
(Second pay oil at 2110')		
(Bridged at 2112')		
Total depth		2128

Make 6" oil week 100 B. tank.

No water.

Short rig, good angle iron.

Center not good. Can be pumped while iron beam D. M. put in.



STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

570

WELL RECORD

Permit No. MAN-520-A

Oil or Gas Well \_\_\_\_\_  
(KIND)

Company Valley Steel Products Co.  
Address St. Louis, Mo.  
Farm John C. Morris Acres 77.608  
Location (waters) Dolls Run  
Well No. 10 Elev. 1372  
District Clay County Monongalia  
The surface of tract is owned in fee by \_\_\_\_\_  
Address \_\_\_\_\_  
Mineral rights are owned by \_\_\_\_\_  
Address \_\_\_\_\_

Drilling commenced \_\_\_\_\_  
Drilling completed \_\_\_\_\_  
Date Shot \_\_\_\_\_ From \_\_\_\_\_ To \_\_\_\_\_  
With \_\_\_\_\_


Open Flow \_\_\_\_\_ /10ths Water in \_\_\_\_\_ Inch  
\_\_\_\_\_ /10ths Merc. in \_\_\_\_\_ Inch  
Volume \_\_\_\_\_ Cu. Ft.  
Rock Pressure \_\_\_\_\_ lbs. \_\_\_\_\_ hrs.  
Oil \_\_\_\_\_ bbls., 1st 24 hrs.  
Fresh water \_\_\_\_\_ feet \_\_\_\_\_ feet  
Salt water \_\_\_\_\_ feet \_\_\_\_\_ feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			
16			Kind of Packer
13			
10	744	Pulled	Size of
8 3/4	1610	1610	
6 5/8	1760	1760	Depth set
5 3/16			
3 1/2	2012	2012	Perf. top
2	2128	2128	Perf. bottom
Liners Used			Perf. top
			Perf. bottom

CASING CEMENTED \_\_\_\_\_ SIZE \_\_\_\_\_ No. Ft. \_\_\_\_\_ Date \_\_\_\_\_

COAL WAS ENCOUNTERED AT \_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
\_\_\_\_\_ FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES  
\_\_\_\_\_ FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Pittsburgh Coal			716				
Light flow of gas at			2008				
More gas			2088				
First pay at oil			2094				
Second pay at oil			2110				
Bridged at			2112				
Total Depth				2128			
Make 6" oil week							
100 B. tank							
No water							
Short rig, good angle iron							
Center not good can be pumped while							
Iron Beam D. M. put in							



PROPOSED MANNER OF PLUGGING AND FILLING WELL

(RECOMMENDED BY RULES AND REGULATIONS)

WEST VIRGINIA DEPARTMENT OF MINES  
OIL AND GAS DIVISION  
WORK ORDER

Well to be plugged and filled as follows:

WORK ORDER PREPARED BY THE DEPARTMENT OF MINES

Total Depth 2120' -- Full 2" casing (1120')

Sole bridges at 2120' -- Fill with clay from bridge to 2020' - 20'  
below 4-7/8" casing

Next Cement 2020' - 2000'  
5' crushed stone on cement plug -- Full 4-7/8" casing  
and continue to fill with clay to 1900'  
Next Cement 1900' - 1800'

Full 6-3/8" casing and

SET A PERMANENT BRIDGE AT 1700' - casing rest of 6-3/8"  
5' crushed stone cement and 5' crushed stone on bridge  
Fill with clay to 1600'

FULL 6-3/8" casing on balance of hole is filled and plugged

Fill with clay from 1600' to 1500'  
Next Cement 1500' - 1400'  
5' crushed stone on cement plug - sealing off all salt water

SET A PERMANENT BRIDGE AT 1200' - approximately bottom of Dunford Sand  
5' crushed stone cement and 5' crushed stone on bridge  
Fill with clay to 1000'

Next Cement 1000' - 1000'  
5' crushed stone on cement plug - sealing off Dunford Sand

Make a 24-hour test for gas - if not present

SET A PERMANENT BRIDGE AT 700' - 50' below Pittsburgh Coal  
Next Cement 700' - 600' - 50' above Pittsburgh Coal  
5' crushed stone on cement and  
Fill with clay to 500' - and suitable plug for fresh water protection  
and fill with clay to surface - Street surface in accordance with Rule 20

If Gas is present - set 2" vent from 700' (50' below P. C.) to surface  
To be installed by Mine Company from 700' around vent to 600' & complete as  
Coal Owner or Operator, stated above.

Comments:

This "work order" is submitted for your approval and concurrence and unless notified of your disapproval or non-concurrence, the undersigned will proceed with the plugging and filling of said well in the above described manner on the date stated in the notice of intention to plug and abandon the said well on opposite side of this sheet.

Very truly yours,

Well Operator

No objections have been filed by the coal owner or coal operator, or any available adjacent lease or property owners or interested by the Department of Mines in the manner herein described for the plugging and filling of the well above mentioned. Therefore, the same is hereby approved this

— 24th day of September, 1923 —

DEPARTMENT OF MINES  
Oil and Gas Division

By: \_\_\_\_\_

NOTE: This "work order" shall be filed in triplicate, one copy for the files of the Department of Mines; one to be approved or corrected and returned to the well operator as the authority for plugging said well; and one for the well operator.

STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

**NOTICE OF INTENTION TO PLUG AND ABANDON WELL**  
(REQUIREMENT OF SECTION 2, ARTICLE 4, CHAPTER 22 OF THE CODE)

To The Department of Mines,  
Charleston, W. Va.

<u>Christopher Seal Company</u> OIL OPERATOR OR OIL OWNER	<u>VALLEY STEEL PRODUCTS COMPANY</u> NAME OF WELL OPERATOR
<u>c/o Geo. E. Flegal, Chief Eng'r.,</u>	<u>c/o Wayne E. Flegal</u>
<u>Parkerson, W. Va.</u> ADDRESS	<u>P. O. Box 6475 - St. Charles, W. Va.</u> OIL WELL ADDRESS
_____	<u>September 3, 1951</u> 19__
_____	_____
<u>_____</u> ADDRESS	_____
_____	<u>Way</u> District
_____	<u>Lincoln</u> County
<u>_____</u> LEASE OR PROPERTY OWNER	<u>Well No. 10</u>
_____	<u>SEP 5, 1951</u> Form

Gentlemen:— **ROBERT INFANTE OLIVER c/o LINCOLN - BERGANTON - TELEPHONE 5867  
24 HOURS IN ADVANCE OF PLUGGING DATE**

The undersigned well operator is about to abandon the above described well and will commence the work of plugging and abandoning said well on the \_\_\_\_\_ day of \_\_\_\_\_, 19\_\_ (which date shall not be less than five days after the day on which this notice so mailed is received, or in due course should be received by the Department of Mines.)

This notice is given you in order that your respective representatives may be present at the plugging and filling of said well. You are further notified that whether you are represented or not represented the undersigned will proceed on that date, or shortly thereafter, to plug and fill said well in the manner required by Section 2, Article 4, Chapter 22 of the Code and given in detail on the reverse side of this notice, in "Work Order."

This notice is being mailed by registered mail to each of you at the above addresses on the above date.

Very truly yours,

VALLEY STEEL PRODUCTS COMPANY  
Well Operator.



NOTE: Upon the abandonment of all wells drilled prior to June 1, 1935, a plat prepared by a competent engineer, showing the name and county in which the tract of land is located, the name and address of owner, the name of the operator and adjacent tracts, and the location of the shaft to be abandoned well, determined by survey, and the address and distance of such well from two permanent points or landmarks on said tract, shall be submitted with this notice.

(Over)