

Clinton District, Monongalia County, W. Va.

Near Uffington.
Well completed March 22, 1900.

	Top.	Bottom.	Thickness.
Conductor	0	- 20	20
Limestone	20	- 36	16
Sand	36	- 56	20
Slate	56	- 80	24
Coal	80	- 81	1
Slate and shell	81	- 146	65
Limestone	146	- 158	12
Slate	158	- 206	48
Sand, bottom hard	206	- 211	5
Slate and shells	211	- 241	30
Limestone	241	- 261	20
Slate	261	- 301	40
Sand, bottom hard	301	- 371	70
Slate	371	- 401	30
Sand	401	- 466	65
Slate	466	- 520	54
Red rock	520	- 530	10
Slate and shells	530	- 600	70
Salt Sand	600	- 675	75
Red rock	675	- 725	50
Limestone	725	- 735	10
Black slate	735	- 775	40
Slate and shells	775	- 800	25
Lime	800	- 850	50
Sand, black (top of Big Injun) (cased on sand at 860')	850	- 860	10
Sand	860	- 990	130
Slate and shells	990	- 1060	70
Sand	1060	- 1190	130
Slate	1190	- 1255	65
Limestone	1255	- 1280	25
Slate and shells	1280	- 1320	40
Sand	1320	- 1336	16
Slate and shells	1336	- 1436	100
Sand, hard	1436	- 1491	55
Slate	1491	- 1496	5
Sand, hard	1496	- 1540	44
Slate and shells	1540	- 1580	40
Red rock and black slate (caving)	1580	- 1835	255
Dark sand	1835	- 1920	85
Slate	1920	- 1930	10
Dark sand with hard streaks (screw of slate every 15 or 20 feet)	1930	- 2030	100
White slate (dark at bottom)	2030	- 2280	250
Total depth		2280	