



# DRILLER'S RECORD

Previously Requested, but NOT AVAILABLE

DATE: 4/10/91

COUNTY PERMIT

fukn 18-4 (Obverse)

(Revised 3- BECEIVED MAR 0 4 1982



W-11	······································	_
Farm	Beeghly Brothers	_
API 7	<b>147 -</b> 077 <b>-</b> 0216	_
Date	March 3, 1982	_

MAR 0 4 1900 STATE OF WEST VIRGINIA

OIL AND GAS DIVISION STATE OF WEST VIRGINIA

ONLY DEPARTMENT OF MINES

### OII AND GAS WELL PERMIT APPLICATION

WELL TYPE: 0il / Gas X /	
(If "Gas", Production/ Unde	rground storage / Deep / Shallow X /
LOCATION: Elevation: 2211 Watershe	d: Glade Run
	Preston Quadrangle: Brandonville
WELL OPERATOR MERT Development Inc	DESIGNATED AGENT   Jerry Poling
	Address Route 8 - Box 336-AA
Address Route 8 - Box 336-AA Fairmont, West Virginia 26554	
OIL AND GAS	
ROYALTY OWNER Beeghly Brothers, Inc.	COAL OPERATOR
Address Route 4 - Box 225	Address
Bruceton Mills, W. Va.	
Acreage 104	OUNTED (C) LUTU DECLADATION ON DECORD
•	COAL OWNER(S) WITH DECLARATION ON RECORD:
SURFACE OWNER James Wright	NAME Beeghly Brothers, Inc.
Address Route 4 - Box E4	Address Route 4 - Box 225
Bruceton Mills, W. Va.	Bruceton Mills, W. Va.
Acreage 104	Address
FIELD SALE (IF MADE) TO:	
NAME	
Address	COAL LESSEE WITH DECLARATION ON RECORD:
	NAME
	Address
OIL AND GAS INSPECTOR TO BE NOTIFIED:	
	•
NAME Bill Blosser	
Address Route 4 - Box 317  Fairmont, West Virginia 26554	
Telephone 363-9105	
•	
The undersigned well operator is entitabove location under a deed / lease X to the undersigned well operator from ME  (If said deed, lease, or other contract has	
Recorded on April 10, , 1981, in the of	
	491 Book at page $340$ . A permit is
requested as follows:	/ Badrill / Eractura or stimulate /
PROPOSED WORK: Drill A / Drill Deeper	/ Redrill/ Fracture or stimulate/ / Perforate new formation/
	well (specify)
. Other physical change in	werr (specially)
planned as shown on the	work order on the reverse side hereof.
The above named coal operator, coal owner(s)	, and coal lessee are hereby notified that any
objection they wish to make or are required	to make by Code \$22-4-3 must be filed with the
Department of Mines within fifteen (15) days	s after receipt of this Application by the Dept
Copies of this Permit Application and the en	nclosed plat and reclamation plan have been
mailed by registered mail or delivered by h	and to the above named coal operator, coal own-
	y of the mailing or delivery of this Applicatio
to the Department of Mines at Charleston, W	est Virginia.
PLEASE SUBMIT COPIES OF ALL	
GEOPHYSICAL LOGS DIRECTLY TO:	ERT Development, Inc.
Druine.	· Well Operator
WEST VIRGINIA OIL AND GAS	A ./ 1
	/:() <sub>1</sub> /3/2
1613 WASHINGTON ST., E.	
CHARLESTON, WV 25311 It Telephone - 304/348-3092	

FORM IV-38 Affidavit of Plugging)

#### STATE OF WEST VIRGINIA DEPARTMENT OF MINES OIL AND GAS WELLS DIVISION

#### AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Department, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

Coal Operator or Ow	mer	N	Reserves Oil Companie of Well Operat	or
t. 4 Box 225. Bruceton			7. Bridgeport, WV	26330
Address			Complete Address	
				19
Coal Operator or Ow	mer	WEL	L AND LOCATION	
en e		Grant		District
Address				
Mrs. James Wright		Preston		County
Lease or Property (	Owner			*
Rt. 4 Box E4, Bruceton		WELL NO.	#4	
Address				
			Beeghly	Farm
	a Rivertile Dona	ld Ellis		
E INSPECTOR SUPERVISING	G PLUGGING Dona	Id EIIIS		
	AFFIDA	/IT		•
E OF WEST VIRGINIA,	001			
ty of <u>Harrison</u>	ss: ——		·	
Thomas P. Sande		and Randy	Underwood	
Thomas P. Sande g first duly sworn acc of plugging and filli	to love dono	se and say that	t they are experie	inced in the
cespectively, well the above well, that s	esid work was comme	ncea on the st	u day 01 250	tember
and that the wel	.I was plugged and	IIIIed In the		
nd or Zone Record	Filling Mat	erial	Plugs Used	Casing
Formation	Swab well to bo	ottom set of pe	rfs. Size & Kind	PULLEDLEFT
				T
	Pump 100' Cemer			
	3,130' to 2,980	) <b>'</b>		
	3,130' to 2,980	)' com 2,980'-1,54	b'	
	3,130' to 2,980 6% HOWCO Gel fr	om 2.980'-1.54 ing at 1.512'-a	b'	
	3,130' to 2,980 6% HOWCO Gel fr Cut 4 1/2" casi pump 100' cemer	om 2.980'-1.54 ing at 1.512'-a	b'	
	3,130' to 2,980 6% HOWCO Gel fr Cut 4 1/2" Casi pump 100' cemer 1,540'-1,440 6% HOWCO Gel fr	om 2.980'-1.54 ing at 1.512' a nt plug from rom 1.440'-1.12	h' nd	
	3,130' to 2,980 6% HOWCO Gel fr Cut 4 1/2" Casi pump 100' cemer 1,540'-1,440 6% HOWCO Gel fr	om 2.980'-1.54 ing at 1.512' a nt plug from rom 1.440'-1.12	h'	
	3,130' to 2,980 6% HOWCO Gel fr Cut 4 1/2" Casi pump 100' cemer 1,540'-1,440 6% HOWCO Gel fr	om 2,980'-1,54 ing at 1,512' a ot plug from	h'	
	3,130' to 2,980 6% HOWCO Gel fr Cut 4 1/2" Casi pump 100' cemer 1,540'-1,440 6% HOWCO Gel fr	om 2.980'-1.54 ing at 1.512' a nt plug from rom 1.440'-1.12	h'	
	3,130' to 2,980 6% HOWCO Gel fr Cut 4 1/2" Casi pump 100' cemer 1,540'-1,440 6% HOWCO Gel fr	om 2.980'-1.54 ing at 1.512' a nt plug from rom 1.440'-1.12	h'	
	3,130' to 2,980 6% HOWCO Gel fr Cut 4 1/2" Casi pump 100' cemer 1,540'-1,440 6% HOWCO Gel fr	om 2.980'-1.54 ing at 1.512' a nt plug from rom 1.440'-1.12	h'	
	3,130' to 2,980 6% HOWCO Gel fr Cut 4 1/2" Casi pump 100' cemer 1,540'-1,440 6% HOWCO Gel fr	om 2.980'-1.54 ing at 1.512' a nt plug from rom 1.440'-1.12	od o' urface	
	3,130' to 2,980 6% HOWCO Gel fr Cut 4 1/2" Casi pump 100' cemer 1,540'-1,440 6% HOWCO Gel fr	om 2.980'-1.54 ing at 1.512' a nt plug from rom 1.440'-1.12	nd o' urface	18/86
Coal Seams	3,130' to 2,980 6% HOWCO Gel frout 4 1/2" casi pump 100' cemer 1.540'-1.440 6% HOWCO Gel from the plug from the pl	om 2.980'-1.54 ing at 1.512' a nt plug from rom 1.440'-1.12	od o' urface	18/86
Coal Seams	3,130' to 2,980 6% HOWCO Gel frout 4 1/2" casi pump 100' cemer 1.540'-1.440 6% HOWCO Gel from the plug from the pl	om 2.980'-1.54 ing at 1.512' a nt plug from rom 1.440'-1.12	Description o	f Monument
ame)	3,130' to 2,980 6% HOWCO Gel frout 4 1/2" casi pump 100' cemer 1.540'-1.440 6% HOWCO Gel from the plug from the pl	om 2.980'-1.54 ing at 1.512' a nt plug from rom 1.440'-1.12	Description of Monument Cap - 8	f Monument 5/8" casing
ame)	3,130' to 2,980 6% HOWCO Gel frout 4 1/2" casi pump 100' cemer 1.540'-1.440 6% HOWCO Gel from the plug from the pl	om 2.980'-1.54 ing at 1.512' a nt plug from rom 1.440'-1.12	Description o  Monument Cap - 8  welded 3' above o  Vented with 2" pi	f Monument  5/8" casing  round level  pe.
ame) ame) ame)	3,130' to 2,980 6% HOWCO Gel frout 4 1/2" casi pump 100' cemer 1.540'-1.440 6% HOWCO Gel from the plug from the pl	om 2.980'-1.54 ing at 1.512' a nt plug from rom 1.440'-1.12	Description of Monument Cap - 8	f Monument  5/8" casing  round level  pe.
ame) ame) ame)	3,130' to 2,980 6% HOWCO Gel frout 4 1/2" Casi pump 100' cemer 1.540'-1.440 6% HOWCO Gel fro Cement plug fro 6% HOWCO Gel fro	com 2.980'-1.54 ing at 1.512' a int plug from or 1.440'-1.12 om 1.120'-1.020 rom 1:020' to s	Description of Monument Cap - 8 welded 3' above of Vented with 2" pi	f Monument 5/8" casing round level pe.
ame) ame) ame) ame) ame) ame) and that the work of	3,130' to 2,980 6% HOWCO Gel frout 4 1/2" cast pump 100' cemer 1.540'-1.440 6% HOWCO Gel fro cement plug fro 6% HOWCO Gel fro 6% HOWCO Gel fro	com 2.980'-1.54 ing at 1.512' a int plug from or 1.440'-1.12 om 1.120'-1.020 rom 1:020' to s	Description of Monument Cap - 8 welded 3' above of Vented with 2" pi	f Monument 5/8" casing round level pe.
ame) ame) ame) ame) ame) ame) and that the work of September	3,130' to 2,980 6% HOWCO Gel frout 4 1/2" cast pump 100' cement 1.540'-1.440 6% HOWCO Gel from Gel fro	com 2.980'-1.54 ing at 1.512' a int plug from or 1.440'-1.12 om 1.120'-1.020 rom 1:020' to s	Description of Monument Cap - 8 welded 3' above of Vented with 2" pi	f Monument 5/8" casing round level pe.
ame) ame) ame) ame) ame) ame) and that the work of	3,130' to 2,980 6% HOWCO Gel frout 4 1/2" cast pump 100' cement 1.540'-1.440 6% HOWCO Gel from Gel fro	com 2.980'-1.54 ing at 1.512' a int plug from or 1.440'-1.12 om 1.120'-1.020 rom 1:020' to s	Description of Monument Cap - 8 welded 3' above of Vented with 2" pi	f Monument 5/8" casing round level pe.
ame) ame) ame) ame) ame) and that the work of September	3,130' to 2,980 6% HOWCO Gel frout 4 1/2" cast pump 100' cement 1.540'-1.440 6% HOWCO Gel from Gel fro	com 2.980'-1.54 ing at 1.512' a int plug from or 1.440'-1.12 om 1.120'-1.020 rom 1:020' to s	Description of Monument Cap - 8 welded 3' above of Vented with 2" pi	f Monument 5/8" casing round level pe.
ame) ame) ame) ame) ame) and that the work of September And further deponent	3,130' to 2,980 6% HOWCO Gel frout 4 1/2" casipump 100' cement 1.540'-1.440 6% HOWCO Gel from	com 2.980'-1.54 ing at 1.512'-a ing at 1.512'-a int plug from  com 1.440'-1.12 om 1.120'-1.020 com 1:020' to s  ing said well	Description of Monument Cap - 8 welded 3' above of Vented with 2" pi	f Monument  5/8" casing  round level  pe.  aber  the _5th day
ame) ame) ame) ame) ame) and that the work of September	3,130' to 2,980 6% HOWCO Gel frout 4 1/2" casipump 100' cement 1.540'-1.440 6% HOWCO Gel from	com 2.980'-1.54 ing at 1.512'-a ing at 1.512'-a int plug from  com 1.440'-1.12 om 1.120'-1.020 com 1:020' to s  ing said well	Description of Monument Cap - 8 welded 3' above of Vented with 2" pill Welded permit numbers completed on the state of the	f Monument  5/8" casing  round level  pe.  aber  the _5th day
ame) ame) ame) and that the work of September  And further deponent	3,130' to 2,980 6% HOWCO Gel frout 4 1/2" casipump 100' cement 1.540'-1.440 6% HOWCO Gel from	com 2.980'-1.54 ing at 1.512'-a ing at 1.512'-a int plug from  com 1.440'-1.12 om 1.120'-1.020 com 1:020' to s  ing said well	Description of Monument Cap - 8 welded 3' above of Vented with 2" pit Welded permit numbers completed on the complete of the c	f Monument  5/8" casing round level pe. the _5th day
ame) ame) ame) and that the work of September  And further deponent orn to and subscribed b	3,130' to 2,980 6% HOWCO Gel frout 4 1/2" cass pump 100' cemer 1.540'-1.440 6% HOWCO Gel fro Cement plug fro 6% HOWCO Gel fro	com 2.980'-1.54 ing at 1.512'-a ing at 1.512'-a int plug from  com 1.440'-1.12 om 1.120'-1.020 com 1:020' to s  ing said well	Description of Monument Cap - 8 welded 3' above of Vented with 2" pill Welded permit numbers completed on the state of the	f Monument  5/8" casing round level pe. the _5th day
ame) ame) ame) ame) and that the work of September  And further deponent	3,130' to 2,980 6% HOWCO Gel frout 4 1/2" cass pump 100' cemer 1.540'-1.440 6% HOWCO Gel fro Cement plug fro 6% HOWCO Gel fro	com 2.980'-1.54 ing at 1.512'-a ing at 1.512'-a int plug from  com 1.440'-1.12 om 1.120'-1.020 com 1:020' to s  ing said well	Description of Monument Cap - 8 welded 3' above of Vented with 2" pit Welded permit numbers completed on the complete of the c	f Monument  5/8" casing round level pe. the _5th day

(Revised 3-81)

## PROPOSED WORK ORDER

# THIS IS AN ESTIMATE ONLY:

ACT	TUAL II	NFORMAT	ION MUST	BE S	UBMITT	ED ON FO	RM 1V-35 I	JPON COMPLET	ION
DRILLING CO	NTRACTO	OR (IF-	KNOWN)		Petrol	eum Easte	ern Develor	oment	
	•	· A	ddress		Vienna	<u> </u>			
					West V	'irginia			
	d depti ate wa ate co being (	h of co ter str al seam mined i	mpleted wata dept depths: n this a	hs:	3850 Fresh, -		feet;	ry X / Cabl	le tools/ feet.
CASING AND CASING OR	TUBING		<u>M</u> Cificati	ONS		FOOTAGE	INTERVALS	CEMENT FILL	1 PACKERS
TUBING TYPE			Weight		•	For Dril	- Left in	UP OR SACKS	
	Size	Grade	per ft	New	Used	<del></del>	Well	Cubic ft.	
	11 3/4	ļ		X	<del> </del>	. 50	50	CTS	Kinds
Fresh water			<del> </del>	ļ	<u> </u>		<u> </u>	<u> </u>	
Coal	1 0 5 10		<b></b>		<del> </del>	1200	1200	CTS	!
	8 5/8		<del> </del>	X	<del> </del>	1200	3700	1500	Depths set
Tubing	4 1/2		<b> </b>	X	<del>                                     </del>		3500	1300	
Liners	2 3/0			<del>                                     </del>	<del>                                     </del>		3300	<del>                                     </del>	Perforations:
2111013	1	1		<u> </u>	1	1			Top Bottom
	i	1						l	
	1							1	
622-4 posed A sep where	-8a fr well. arate fract	om the Form IV uring o	owner of -2 shall r stimul	any not ating	water be red is to	well or quired fo o be part	dwelling of r fractur of the w	within 200 fe ing or stimu	uired by Code eet of the pro- lating a well h a permit is herewith.
_									
THIS PERMIT /	nout DE	rusies A	VE THE WELL	L SITE,					
ALL PROVISIO	NO MIN	G IN ACC	ORDANKE!	WITH (	HAPTER	22			
	T 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	がえん アンシャ	the state of the						
	A. Arr		Mark to a second	Service Co.		<b>7</b>			
PROFERATION	S HAVE	Mee so	energy Pitting J		SHALL B	APIRE			
# OFFRATION				/ 11	-8-82				
		The second secon		)		·			
or co is to  The undersig	al les he is ned co	see who sued wi	has rec thin fif	teen  / own sed w	1 a dec (15) W A I her_ ell lo	claration $days$ of $x$ $\frac{V}{I} = \frac{R}{I}$ $\frac{E}{I} = \frac{R}{I}$ $\frac{E}{I} = \frac{R}{I}$	under Co receipt th e/ of If a mine	de \$22-4-20, ereof: the coal und map exists	any coal owner if the permit ler this well which covers the
signed has n	o obje or has	compli	to the wo	ork p	ropose	d to be	done at th	nis location,	nap. The under- provided the Virginia Code and
Date:		, 1	9						
					F	Bv:			