



New Location
 Well Deeper
 Abandonment

Vol. XVII, p. 646

4.24 S
 0.13 W
 6 SE (I-4)

Company Geoffrey L. Cabot Inc.
 Address 900 Union Bldg. Charleston, W. Va.
 Farm Eva Carney
 Tract _____ Acres 56 1/2 Lease No. 3-846
 Well (Farm) No. 1 Serial No. 1075
 Elevation (Spirit Level) 1101.61'
 Quadrangle Winfield - E.C.
 County Putnam District Union
 Engineer Ray Booton
 Engineer's Registration No. _____
 File No. _____ Drawing No. _____
 Date 9-17-42 Scale 1" = 660'

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. Put-208

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.
 - Denotes one inch spaces on border line of original tracing.

6-0-112 Deep Well ✓

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
W E L L R E C O R D

Permit No. Put 208
Winfield Quad.

Gas Well
CASING & TUBING

Company	Godfrey L. Cabot, Inc.		
Address	Charleston, W.Va.	10 $\frac{1}{2}$	1072 Same
Farm	Eva Carney Acres	8 5/8	2313
Location		7	5131 Same
Well No	Ser. 1075 -# 1	Elev. 1090.12 2 3/8	5271 Same
District	Union Putnam County	10 $\frac{1}{2}$ coupling shoe	
Commenced	Oct. 12, 1942	8 5/8 Spang Gas Anchor	
Completed	Jan. 1, 1943	Packer-25 bags aquagel	
Date shot	Jan. 6, 1943 with 40 qts. Depth	7" OD Spec. Orisk.	
	5217-5237 Gauge B.S. 215 M; B.H. Packer-40 bgs. Agg.		
	40 Mins. A.S. 1,400 M	Line pipe as tubing. Bottom	
Volume	1400 MCF A.S.	joint welded.	
Rock Pressure	1900 lbs. 94 hrs. 135'		
Fresh Water	1/4 Blr. pr. hr.; 940' level 900';	Tubed and shut	
Salt Water	1173' 2 blr. pr. hr.; 1370' 2 blr. in 1-8-43		
	pr. hr.; 1455' 1 $\frac{1}{2}$ " pr. hr.	Perf. top 5217 - 5266	
	Water H.F. 1820'	" bot 5223 5273	

Soil	0	8	-Slate	2080	2082
Sand, Red Rock	8	230	-Big Lime	2082	2238
White Slate & Sand	230	280	Slate & Shells	2238	2290
Red Rock	280	290	-Sand	2290	2302
Slate & Shells	290	375	Lime	2302	2318
Red Rock & Sand	375	455	Slate & Shells	2318	2715
Lime	455	495	-Brown Shale	2715	2723
Red Rock	495	500	-Berea Grit	2723	2738
Lime	500	530	Slate & Lime	2738	3960
White Slate	530	536	Brown Shale 813	3960	4015
Lime	536	545	Slate & Shells	4015	4200
White Slate	545	560	Brown Shale	4200	4262
Red Rock	560	580	Slate & Shells	4262	4375
Lime	580	615	Brown Shale	4375	4475
White Slate	615	679	Slate & Shells Cr -20	4475	4868
Lime	679	700	Brown Shale	4868	5090
Red Rock	700	705	-Black Shale	5090	5111
Gritty Lime	705	725	-Corniferous Lime	5111	5212
White Slate	725	740	Oriskany Sand	5212	5240
Red Rock	740	805	Black Lime	5240	5243
Sand	805	840	Oriskany Sand	5243	5266
White Slate	840	850	-Lime	5266	5275
Red Rock	850	915	S.L.M. 5131		
White Slate	915	940			
Lime	940	965	Gauges in Oriskany Sand A.S		
Slate	965	968	Gauge B.S. 215 M		
Lime	968	990	5 Min. A. S.	1865 M	
Red Rock	990	1000	10 "	1565 M	
Lime	1000	1065	15 "	1485 M	
Sand	1065	1081	20 "	1443 M	
White Slate	1081	1100	40 "	1440 M	
Sand	1100	1185			
White Slate	1185	1199	5219	200 M	
Lime	1199	1205	5220	84 M	
White Slate	1205	1240	5224	411 M	
Lime	1240	1269	5229 -5236	169 M	
White Slate	1269	1403	5247	158 M	
Sand	1403	1467	5266	146 M	
White Slate	1467	1480	5275	133 M	
Sand	1480	1541			
White Slate	1541	1620			
Gritty Lime	1620	1640			
Dark Slate	1640	1670			
Sand	1670	1692			
White Slate	1692	1765			
Salt Sand	1765	1986			
Black Lime	1986	1994			
Sand	1994	2040			
Lime	2040	2058			
Slate	2058	2060			
Lime	2060	2080			

5266
1090

4176

5111
1090

4021