





Rosenburger, Spindle & Yancey #1

This well ~~was~~ located about  
2 miles below Minfield, Putnam  
County, West Virginia, located  
as shown on this photostat  
which is taken from the  
Minfield Quadrangle.

#65

File in Putnam Records 65

(Report now known as) Rosenberger, Spindle & Yancey (well no. 1)

RECORD of Well drilled by Messrs. Grosscup - Located in Putnam County on Kanawha, north side of Kanawha River, west of Red House, West Virginia, near mouth of Buffalo Creek. (old site of Putnam - on - Kanawha)

Well completed 1920 - ELEVATION 590 feet

Soil	00	10
Red Clay	10	20
Sand	20	40
Red Rock	40	70
Quick Sand	70	80
Red Rock	80	100
Sand	100	120
Blue Slate	120	150
Red Rock	150	175
Slate	175	200
Sand	200	240
White Slate	240	250
Red Rock	250	290
Blue Slate	290	335
Sand	335	350
Slate	350	360
Sand	360	400
Red Rock	400	420
Sand	420	440
Red Rock	440	450
Lime	460	470
Slate	470	490
Coal	490	495
Sand	495	555
Slate	555	580
Sand	580	620
Slate	620	650
Sand	650	670
Slate	670	690
Sand	690	720
Slate	720	740
Lime	740	770
Sand	770	825
Black Slate	825	830
Sand	830	845
Slate	845	855
Salt Sand	855	980
White Slate	980	1000
Salt Sand	1000	1060
Slate	1060	1132
Sand	1132	1202
Slate	1202	1262
Marion Sand	1262	1427

Yancey #77

Slate	1427	1452
Little Lime	1452	1475
Pencil Cave	1475	1478
Big Lime	1478	1625
Slate and Shells	1625	1658
<u>Keener Sand</u>	1658	1675
Slate	1675	1692
Big Injun	1692	1760
Slate	1760	1767
Black Lime	1767	1780
Slate and Shells	1780	1870
<u>Squaw Sand</u>	1870	1905
Slate and Shells	1905	2148
Coffee Slate	2148	2168
Berea Grit	2168	2196
Slate	2196	2210
Lime	2210	2245
White Slate	2245	2253
Slate and Lime	2253	2380
Sand	2380	2400
Slate and Shells	2400	2533 - GAS 2535' - 2536'
Sand	2536	2537
Slate and Shells	2537	3251
TOTAL DEPTH		3251'

Drilled by J. W. Ramsey - Drillers: Fred English  
Earl Hartley

Commenced spudding October 17, 1920

13" Conductor 16 feet (in)

10" Casing 60 feet (in)

8 1/4" Casing 360 feet (Pulled - Packer)

6-5/8" Casing 1492 feet (in)

5-3/16" " 1772 feet (in)

Fresh water in 13" hole 60 feet

Fresh water in 10" hole 400 feet - 3 bailers per hour (150 gals per hour)

Fresh water in 10" hole 600 feet - 3 bailers per hour

hole full of water at 950 feet - 1018 bailed clean

Hole full of water at 1060 feet

Water at 1336 - ran over top of casing

Water in Big Injun Sand at 1694 feet.

*This copy rec'd from David B. Drapler, Research  
Assistant, Fed. Civil Works Ad. & W. Va. Employment  
Relief Administration, Charleston W. Va., - April 21, 1934.  
see his letter in "A.S." file of Apr. 20, 1924. (Encs)*

Scott District, Putnam County, W. Va.  
Drilled by Winsett Oil and Gas Co., Guyandot Land Assoc.  
Elevation, 610'.  
Well completed, March 1, 1909.  
250,000 cu. ft. gas. (Berea Sand).

	Top.	Bottom.
Gas Sand	605	- 780
Salt Sand	960	- 12305
Little Lime	1336	- 1350
Pencil Cave	1350	- 1360
Big Lime	1360	- 1565
Big Injun Sand	1600	- 1680
Berea Sand (gas pay, 2070-2080')	2066	- 2092

Scott District, Putnam County, W. Va.  
Guyan Oil Co.

Located  $1\frac{1}{2}$  mi. S.  $85^{\circ}$  E. from Scott Depot.

Elevation, 610' L.

Record furnished by W. J. Roger, Supt., Guyan Oil Co., Huntington, W. Va.

	Top.	Bottom.
Unrecorded (8 bailers water at 450')	0	605
Gas Sand	605	780
Unrecorded	780	960
Salt Sand (hole full water, 1030')	960	1305
Unrecorded	1305	1336
Little Lime	1336	1350
Pencil Cave	1350	1360
Big Lime	1360	1565
Unrecorded	1565	1600
Big Injun Sand	1600	1680
Unrecorded	1680	2066
Berea Sand (gas at <sup>2070-</sup> 2080'; 248,000 cu.ft.)	2066-	2092

14

Scott District, Putnam County, W. Va.  
 Guyan Oil Co., Huntington, W. Va. (W.J. Roger, Supt.)  
 Located 1½ mi. S. 85° E. from Scott Depot.  
 Elevation, 610' L.

	Top.	Bottom.
Unrecorded (8 bailers water at 450')	0	605
Gas Sand	605	780
Salt Sand (hole full of water at 1030')	960	1305
Little Lime	1336	1350
Pencil Gave	1350	1360
Big Lime	1360	1565
Big Injan Sand	1600	1680
Berea Sand (248,000' gas at 2080')	2666	2092