

CO: 081 PMT: 184
Loc Digitized from OGIS 7.5' Mylar
QUAD: 325 DATE: 9-FEB-90
LAT: 37 55.0 Miles South: 1.31
LONG: 81 22.5 Miles West : 0.85

+ Topo. Loc.

Longitude 81 20

ROWLAND LAND CO.
C-2026
6106 AC.

Lem Fr. of Sycamore Creek

MICHIGAN E. W. VA.
LAND & MINING CO.

COORDINATES
N. 60967.98
W. 36825.57

Loc. #29

N. 81° 47' W.
6977.5'

N. 47° 40' W.
5316.9'

N. 45° 55' E.
3936.5'

C.C. DICKINSON

#2066A
Paper, Dogwood
Maple & Birch Trs. on
Bank of Workman Cr.

N. 51° 26' W.
145.1'
Stk.

Two-08.
Stumps on
Ridge

Corrected 15' loc.
1.31 S
2.12 W

1.37 S
3.25 W

New Location
Drill Deeper
Abandonment

Company COLUMBIAN CARBON CO.
Address BOX 873 CHARLESTON W.VA.
Farm ROWLAND LAND CO.
Block No. 6
Tract Pt. 574 Acres 6106 AC Lease No. C-2026
Well (Farm) No. 29 Serial No. GW-1167
Elevation (Spirit Level) 2053.3
Quadrangle ECCLES-5-S 133 W. 324
County RALEIGH District CLEAR FORK
Engineer [Signature]
Engineer's Registration No. 2014
File No. _____ Drawing No. WVA-6-51
Date MARCH-16-1951 Scale 1"=1320'

STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION
CHARLESTON

WELL LOCATION MAP
FILE NO. RAI-184

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
W E L L R E C O R D

Permit No. Ral-184
Eccles Quad.

Dry Well

CASING & TUBING

Company Columbian Carbon Company
Address Box 873, Charleston 23, W.Va.
Farm Rowland Land Co. Acres 6106
Location LenFork, Sycamore Creek
Well No. 29 GW-1167 Elev. 2053.3'G
District Clear Fork County Raleigh
Surface Rowland Land Co.
Mineral Same
Commenced 4/10/51
Completed 7/23/51
Fresh water 15'

| | | |
|---------|---------|--------|
| 14" | 27' | 27' |
| 10-3/4" | 757'4" | Pulled |
| 8-1/4" | 2191'1" | pulled |
| 7" | 2641'1" | Pulled |

Coal 779' 24"
856' 24"

| | | | |
|-----------------------|-------|------|---------------|
| Sand, Slate & Lime | 0 | 779 | |
| Coal | 779 | 781 | |
| Slate & Sand | 781 | 856 | |
| Coal | 856 | 858 | |
| S and | 858 | 908 | |
| Lime | 908 | 924 | |
| Sand & Slate | 924 | 1015 | |
| Lime | 1015 | 1030 | |
| Sand & Slate | 1030 | 1150 | |
| Lime | 1150 | 1174 | |
| Sand & Slate | 1174 | 1288 | |
| Coal | 1288 | 1292 | |
| Slate | 1292 | 1415 | |
| Lime | 1415 | 1425 | |
| Sand & Slate | 1425 | 1467 | |
| Lime | 1467 | 1489 | |
| Sand | 1489 | 1517 | |
| Lime | 1517 | 1523 | |
| S and & Slate | 1523 | 1580 | |
| Lime & Shells | 1580 | 1606 | |
| Red Rock | 1606 | 1631 | |
| Lime | 1631 | 1687 | |
| S late | 1687 | 1706 | |
| Lime | 1706 | 1735 | |
| Slate | 1735 | 1837 | |
| Sand | 1837 | 1853 | |
| Slate | 1853 | 1867 | |
| Lime | 1867 | 1895 | |
| Red Rock | 1895 | 2140 | |
| Lime | 2140 | 2196 | |
| Red Rock | 2196 | 2208 | |
| Lime | 2208 | 2229 | |
| Red Rock | 2229 | 2324 | |
| Lime | 2324 | 2419 | |
| Sand (W) | 2419 | 2509 | |
| Lime | 2509 | 2601 | |
| Slate | 2601 | 2617 | |
| Lime < BR? | 2617 | 2921 | Gas 2875 show |
| -Injun Sand | 2921 | 2971 | |
| Lime | 2971 | 3018 | |
| Sand | 3018 | 3030 | |
| Lime & Shells | 3030 | 3070 | |
| -Sand (Weir) | 3070 | 3138 | |
| Slate & Shells | 3138 | 3227 | |
| Lime | 3227 | 3353 | |
| Total Depth | 3353' | | |

Dry hole, plugged & abd. 8/10/51

Casing Record

5/7/51 10-3/4 casing not aquagelled. C.C.C. crew.
6/16/51 8-5/8 casing not aquagelled. C.C.C. crew.
6/28/51 7" casing not aquagelled. C.C.C. crew.