

Latitude 37° 55' 37 52 30

Longitude 81° 27' 30" 25

R. M. HUNTER

ROWLAND LAND CO.

N42°30'E 710'
Sik. Forke Branch Willow Point
Sm. Beech

S46°45'W 630'
3869 * N87°W 380'
N10°30'E 460'
Maple

3.3 W
4.845

1.965

A. A. LILLY

N23°30'E 640'
Sik. Sm. White Oak Pin.

PEACH CREEK

L. L. CANTERBERRY

New Location..
Drill Deeper.....
Abandonment.....

Company UNITED FUEL GAS Co.
 Address CHARLESTON, W. VA.
 Farm ROWLAND LAND Co.
 Tract _____ Acres 137 Lease No. 29199
 Well (Farm) No. _____ Serial No. 3869
 Elevation (Spirit Level) 1330.0 BAR.
 Quadrangle ECCLES
 County RALEIGH District MARSH FORK
 Engineer Stephen R. Spence
 Engineer's Registration No. 2529
 File No. 70-23 Drawing No. _____
 Date 2-29-56 Scale 1"=400'

STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION
CHARLESTON

WELL LOCATION MAP
FILE NO. RAL-2-A

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.
 - Denotes one inch spaces on border line of original tracing.

66

(0)

ROWLAND LAND CO. NO. 3869 WELL.

Marsh Fork District, Raleigh County, W. Va.

By United Fuel Gas Co., Box 1273, Charleston, 25, W. Va.

Abandoned under permit Hal-2; Seales Quadrangle.

On 137 acres, on Peach Creek.

Elevation, 1330' L.

Minerals owned by Rowland Land Co., Box 586, St. Albans, W. Va.

Drilling commenced March 28, 1929; completed June 20, 1929.

Well was not shot.

Open flow, 5/10ths W. in 2". Volume, 94,000 cu. ft. Rock pressure, 515 lbs.

Fresh water at 1663-1666', 3 bailers per 24 hrs.

10" casing, 342'; 8 1/2" tubing, 1363'; 3" tubing, 1608'; all left in.

Anchor packers, 1 x 3 x 10 and 3 x 8 1/2 x 16, set at 1589 and 1549'.

Coal was encountered at 412-414, 695-700, and 805-810'.

Gas well. Record to Dept. of Mines dated March 2, 1956.

Record to RCY from Mrs. Griffith March 28, 1957. Old File No. 44.

	Top.	Bottom.
Gravel	0	10
Sand	10	84
Slate	84	88
Sand	88	160
Slate	160	213
Sand	213	282
Slate	282	286
Sand	286	412
Coal	412	414
Slate and shells	414	434
Sand	434	636
Slate and shells	636	695
Coal	695	700
Sand	700	724
Slate and shells	724	760
Sand	760	775
Slate	775	790
Sand	790	805
Coal	805	810
Slate and lime shells	810	930
Lime	930	980
Slate	980	1050
Sand	1050	1072
Slate	1072	1140
Lime	1140	1295
Red rock	1295	1360
Lime	1360	1370
Red rock	1370	1408
Lime	1408	1428
Red rock	1428	1485
Lime	1485	1524
Slate	1524	1549
Sand (Gas) (gas, 1570-1581', 4/10 W. 2", 84 M.) (gas, 1581-1588', 5/10 W. 2", 94 M.)	1549	1683
Total depth		1683

Hole filled and plugged back to total depth now 1608



44

STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION

Quadrangle Eccles

WELL RECORD

Permit No. Rai 2 A


Oil or Gas Well Gas
(KIND)

Company UNITED FUEL GAS COMPANY
Address P.O. Box 1273, Charleston 25, W. Va.
Farm Rowland Land Co. Acres 137
Location (waters) Peach Creek
Well No. 3869 Elev. 1330'
District Marsh Fork County Raleigh
The surface of tract is owned in fee by _____
Address _____
Mineral rights are owned by Rowland Land Co.
Box 586 Address St. Albans, W. Va.
Drilling commenced 3-28-29
Drilling completed 6-20-29
Date Shot Not shot From _____ To _____
With _____
Open Flow 5 /10ths Water in 2 Inch
_____ /10ths Merc. in _____ Inch
Volume 94,000 Cu. Ft.
Rock Pressure 515 lbs. _____ hrs.
Oil _____ bbls., 1st 24 hrs.
Fresh water 1663-1666' feet _____ feet
Salt water _____ feet _____ feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16			<u>Anchor & Anchor</u>
13			<u>1x3x10" &</u>
10		<u>342'</u>	Size of
8 1/4		<u>1363'</u>	<u>3x8-1/4x16"</u>
6 5/8			Depth set
5 3/16			<u>1589' & 1549'</u>
3		<u>1608'</u>	Perf. top
2			Perf. bottom
Liners Used			Perf. top
			Perf. bottom

CASING CEMENTED _____ SIZE _____ No. Ft. _____ Date _____
COAL WAS ENCOUNTERED AT 412 FEET 24 INCHES
695 FEET 60 INCHES 805 FEET 60 INCHES
_____ FEET _____ INCHES _____ FEET _____ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Gravel			0	10			
Sand			10	84			
Slate			84	88			
Sand			88	160			
Slate			160	213			
Sand			213	282			
Slate			282	286			
Sand			286	412			
Coal			412	414			
Slate & Shells			414	434			
Sand			434	636			
Slate & Shells			636	695			
Coal			695	700			
Sand			700	724			
Slate & Shells			724	760			
Sand			760	775			
Slate			775	790			
Sand			790	805			
Coal			805	810			
Slate & Lime Shs.			810	930			
Lime			930	980			
Slate			980	1050			
Sand			1050	1072			
Slate			1072	1140			
Lime			1140	1295			
Red Rock			1295	1360			
Lime			1360	1370			
Red Rock			1370	1408			
Lime			1408	1428			
Red Rock			1428	1485			
Lime			1485	1524			
Slate			1524	1549			
Sand (Gas) <u>Maxton</u>			1549	1683			
Total depth			1683				
Hole filled & plugged back to total depth now				1608			



Gas 1570-1581' 4/10 W 2" 84 M
Gas 1581-1588' 5/10 W 2" 94 M
Water 1663-1666', 3 bailers per 24 hours.

