



- New Location .
- Drill Deeper . . . .
- Redrill . . . . .
- Abandonment . . . . .

Company P. & J. DEVELOPMENT CO., INC.  
 Address HAMLIN, W. VA.  
 Farm J. A. GANDEE  
 Tract Acres 131 1/2 Lease No. \_\_\_\_\_  
 Well (Farm) No. 10 Serial No. U-2769  
 Elevation (Spirit Level) 803  
 Quadrangle WALTON  
 County ROANE District WALTON  
 Engineer Paul E. Joachim  
 Engineer's Registration No. 669  
 File No. 76-79 Drawing No. \_\_\_\_\_  
 Date SEPT. 25, 1961 Scale 1" = 400'

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON  
**WELL LOCATION MAP**  
 FILE NO. ROA-1084-R

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.  
 — Denotes one inch spaces on border line of original tracing.

*(located as microfilm under 87-30611)*

Walton District, Roane County, W. Va.

By The Ohio Fuel Oil Co.

Drilling commenced July 21, 1910, and completed Aug. 26, 1910.

Contractor, Pratt Drilling Co., Charleston, W. Va.

Drillers, T. B. Tompson and F. E. Sackrider.

Conductor, 16'.

Well shot Aug. 25, 1910, with 40 qts.

1st day's production, 20 bbls.

32 days gas and water.

Examined and approved by F. H. Lange, Foreman.

Copied from Record Books of The Ohio Fuel Oil Co. by C. E. Krebs,

Nov. 13, 1911.

	Top.	Bottom.	Thickness.
Conductor	0	- 16	16
Sand	16	- 20	4
Shelly	20	- 280	260
Red rock	280	- 700	420
Slate	700	- 715	15
Big Dunkard Sand	715	- 840	125
Sand	840	- 900	60
Big slate	900	- 960	60
Sand	960	- 1035	75
Slate	1035	- 1045	10
Sand and slate	1045	- 1260	215
Big shale	1260	- 1320	60
Slate	1320	- 1345	25
Salt Sand (water, 1370'; big water, 1440')	1345		
Sand	1440	- 1600	160
Break	1600	- 1605	5
White sand	1605	- 1670	65
Marion Sand	1670	- 1692	22
Little Line	1692	- 1702	10
Pencil Cave	1702	- 1710	8
Big Line	1718		
Big Injun Sand	1843		
Total depth			1878