

LATITUDE

38 40

02 18

LONGITUDE

→ 7.5' loc  
10/28/29

7.5' ~~loc~~ topo location

7.5' loc	<u>2.495</u>	15' loc	_____
	<u>1.19 W</u>	(calc.)	_____

Company \_\_\_\_\_

Farm \_\_\_\_\_

Elevation 900' ~~Topo map~~  
Estimate!

Quad Looneyville

County \_\_\_\_\_

District Walton

WELL LOCATION MAP

File No. Roane 70062

Walton District, Roane County, W. Va.

By The Ohio Fuel Oil Co.

Rig commenced Nov. 6, 1909, and completed Nov. 14, 1909.

Drilling commenced March 14, 1910, and completed April 23, 1910.

Contractor, Pratt Drilling Co., Charleston, W. Va.

Drillers, Clarence Stewart.

1st day's production, 77½ bbls.

Examined and approved by Ellis Hamrick, Foreman.

Copied from Record Books of The Ohio Fuel Oil Co., by C. E. Krebs,  
Nov. 14, 1911.

	Top.	Bottom.	Thickness.
Conductor	0	- 16	16
Lime	7	- 12	5
Sand and slate	12	- 215	203
Red rock	215	- 360	145
Lime	360	- 375	15
Slate and sand	375	- 425	50
Slate	425	- 435	10
Sand	435	- 680	245
Little Dunkard Sand	680	- 765	85
Coal	765	- 767	2
Lime	767	- 780	3
Big Dunkard Sand (water, 825')	780	- 875	95
Slate and sand	875	- 1235	410
Black sand	1235	- 1350	115
Salt Sand (water, 1440')	1350		
Little Lime	1683	- 1712	29
Pencil Cave	1712	- 1721	9
Big Lime	1721	- 1823	102
Big Injun Sand (oil, 1862')	1844	- 1884	40
Total depth		1886	