

LATITUDE

3840

0218

LONGITUDE

→ 7.5' loc
K19812191

7.5' ~~0.10~~ topo location

| | | | |
|----------|--------------|---------|-------|
| 7.5' loc | <u>2.175</u> | 15' loc | _____ |
| | <u>1.140</u> | (calc.) | _____ |

Company _____

Farm FP Kelly 1 (176)

Elevation 815' ~~815'~~ Topo Est.

Quad Looneyville

County _____

District Walton

WELL LOCATION MAP

File No. Roane 70166

70166

Walton District, Roane County, W. Va.

By The Ohio Fuel Oil Co.

Rig commenced May 22, 1910, and completed May 29, 1910.

Drilling commenced June 15, 1910, and completed Aug. 2, 1910.

Contractor, Pratt Drilling Co., Charleston, W. Va.

Drillers, Edward Umstott and James Devore.

Conductor, 16'.

Well shot Aug. 2, 1910.

1 - 20 H. P. Reid Engine, No. 5794.

Examined and approved by E. H. Lange, Foreman.

Copied from Record Books of The Ohio Fuel Oil Co. by C. E. Krebs

Nov. 13, 1911.

| | Top. | Bottom. | Thickness. |
|--------------------------|------|---------|------------|
| Conductor | 0 | - 16 | 16 |
| Red rock | 16 | - 155 | 139 |
| Sand | 155 | - 220 | 65 |
| Red rock | 220 | - 410 | 190 |
| Lime | 410 | - 430 | 20 |
| Red rock | 430 | - 512 | 82 |
| Lime | 512 | - 532 | 20 |
| Slate | 532 | - 542 | 10 |
| Sand | 542 | - 585 | 43 |
| Shelly | 585 | - 660 | 75 |
| Little Dunkard Sand | 660 | - 760 | 100 |
| Slate | 760 | - 785 | 25 |
| Shells | 785 | - 820 | 35 |
| Big Dunkard Sand | 820 | - 910 | 90 |
| Black slate | 910 | - 920 | 10 |
| Lime | 920 | - 945 | 25 |
| Sand | 945 | - 1060 | 115 |
| Slate | 1060 | - 1117 | 57 |
| Sand | 1117 | - 1250 | 133 |
| Black slate | 1250 | - 1360 | 110 |
| Salt Sand (water, 1465') | 1360 | - 1687 | 327 |
| Little Lime | 1687 | - 1720 | 33 |
| Pencil Cave | 1720 | - 1730 | 10 |
| Big Lime | 1730 | - 1835 | 105 |
| Big Injun Sand | 1835 | - 1891 | 56 |