

LATITUDE

3840

02 18

LONGITUDE

→ 7.5' loc
class 12/91

7.5' ~~loc~~ topo location

7.5' loc	<u>2.23 S</u>	15' loc	_____
	<u>1.04 W</u>	(calc.)	_____

Company _____

Farm FP Kelly 2 (191)

Elevation ~~865~~ 865' Topo Est.

Quad Looneyville

County _____

District Walton

WELL LOCATION MAP

File No. Roane 70167

70167

Walton District, Roane County, W. Va.

By The Ohio Fuel Oil Co.

In Johnson Creek field.

Drilling commenced Oct. 22, 1910, and completed Nov. 30, 1910.

Cost per foot, \$1.00.

Contractor, Pratt Drilling Co., Charleston, W. Va.

Well shot Nov. 29, 1910, with 40 qts.

Conductor, 16'.

Examined and approved by E. H. Lange, Foreman.

Copied from Record Books of The Ohio Fuel Oil Co. by C. E. Krebs

Nov. 15, 1911.

	Top.	Bottom.	Thickness.
Red rock lime	0	- 70	70
Sand	70	- 100	30
Red rock lime	100	- 145	45
Sand	145	- 248	103
Lime and slate	248	- 300	52
Red rock lime	300	- 420	120
Lime and sand	420	- 515	95
Sand, lime, and slate	515	- 760	245
Dunkard Sand	760	- 825	65
Black slate	825	- 840	15
Sand, lime, and slate	840	- 960	120
Sand and slate	960	- 1170	210
Sand and lime	1170	- 1260	90
Slate, sand, and lime	1260	- 1390	130
Salt Sand (big water, 1500')	1395		
Little Lime	1730	- 1770	40
Pencil Cave	1770	- 1774	4
Big Lime	1774	- 1901	127
Big Injun Sand (gas at 1908'; oil at 1919')	1901	- 1938	37
Total depth		1938	

OSCAR KELLEY NO. 1 WELL.

1423
No. On May. (H 243
W.C. Co. (pt))

70168

Harper District, Roane County, W. Va.
Carter Oil Co.
On Cox Fork of Flat Fork, 2-3/4 ml. S. W. of Vandalia.
Completed, March 26, 1909.
Elevation, 815' H.
13" casing, 32'; 10", 583'; 8", 979'; 5-5/8", 1507'; 5-3/16", 2014'.

	Top.	Bottom.
Sand, Cow Run (Dunkard)	915	920
Salt Sand	1365	1390
Salt Sand (gas, 1569'; gas and oil, 1587'; water, 1625')		1563
Total depth		2675