

COPY

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

COALQUEST DEVELOPMENT, LLC
Coal Operator or Owner
2708 CRANBERRY SQUARE MORGANTOWN, WV 26508
Address
COALQUEST DEVELOPMENT, LLC
Coal Operator or Owner
2708 CRANBERRY SQUARE MORGANTOWN, WV 26508
Address
ELVA G. WOLFE
Lease or Property Owner
2741 CURVE BRIDGE ROAD, GRAFTON, WV 26354
Address

ICG TYGART VALLEY, LLC
Name of Well Operator
2708 CRANBERRY SQUARE MORGANTOWN, WV 26508
Complete Address
THORNTON (638)
Well Location
KNOTTSVILLE
District
TAYLOR
County
CNGP-6021
Well No.
WOLFE, IRIS
Farm

STATE INSPECTOR SUPERVISING PLUGGING

Cement Injection 3-18-15

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

RALPH HARMAN and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by ICG Tygart Valley, LLC well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 9th day of March, 2015 and that the well was plugged in the following manner:

Formation	Filling Material	Casing Size & Kind	Casing Pulled	Casing Left In
Cleaned 3 1/2" hole through 4 1/2" casing from Surface to 3520'. Cemented bottom hole plug from 3520' to 1540' with 150 sacks of Expandable Cement. Tagged top of bottom hole plug at 1540'. Removed 1288' of 4 1/2" casing from Surface to 1288'. Left an unknown amount of 4 1/2" casing in the hole from 1288' to an unknown depth. Cleaned 7 7/8" hole from Surface to 1288'. Cleaned 7 7/8" hole through the Lower Kittaning Coal seam from 751' to 756'. Left 1020' of 8 5/8" casing in the hole from Surface to 1052'. Section milled 32' of 8 5/8" casing from 737' to 769'. Left 5' of 16" conductor casing in the hole from Surface to 5'.		16" Conductor Casing	0'	5'
		8 5/8" Casing	Milled 32'	1020'
		4 1/2" Casing	1288'	Unknown
<u>Cemented hole from the top of the bottom hole plug at 1540' back to Surface as follows:</u> From 1540' to 1156' with 40 sacks of Expandable Cement. From 1156' to 651' with 145 sacks of Thixotropic Cement with green dye. From 651' back to the Surface with 155 sacks of Expandable Cement. Cement did circulate at the Surface.		RECEIVED Office of Oil and Gas MAR 23 2015 WV Department of Environmental Protection		
<u>Coal Seams</u>	<u>Description of Monument</u>			
<u>LOWER KITTANING</u>	751' to 756'	77" of 7" casing w/company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to the cement plug at ground level.		
(Name)				
(Name)				
(Name)				

... And that the work of plugging and filling said well was completed on the 17th day of March, 2015

And further deponents saith not.

Ralph Harman
Ralph Harman

Kevin S. Wright
Kevin S. Wright

Sworn to and subscribed before me this 17th day of March 2015

Carole A. Mayle
Notary Public

My commission expires: 9-12-17

Permit No. 47-91-00168-P
Well No. CNGP-6021

03/27/2015

