



---

west virginia department of environmental protection

---

Office of Oil and Gas  
601 57<sup>th</sup> Street, S.E.  
Charleston, WV 25304  
(304) 926-0450  
fax: (304) 926-0452

Harold D. Ward, Cabinet Secretary  
[www.dep.wv.gov](http://www.dep.wv.gov)

Wednesday, June 11, 2025  
WELL WORK PLUGGING PERMIT  
Vertical Plugging

DIVERSIFIED PRODUCTION LLC  
101 MCQUISTON DRIVE

JACKSON CENTER, PA 16133

Re: Permit approval for LOIS A. BAKER 2  
47-091-01068-00-00

This well work permit is evidence of permission granted to perform the specified well work at the location described on the attached pages and located on the attached plat, subject to the provisions of Chapter 22 of the West Virginia Code of 1931, as amended, and all rules and regulations promulgated thereunder, and to any additional specific conditions and provisions outlined in the pages attached hereto. Notification shall be given by the operator to the Oil and Gas Inspector at least 24 hours prior to the construction of roads, locations, and/or pits for any permitted work. In addition, the well operator shall notify the same inspector 24 hours before any actual well work is commenced and prior to running and cementing casing. Spills or emergency discharges must be promptly reported by the operator to 1-800-642-3074 and to the Oil and Gas Inspector.

Upon completion of the plugging well work, the above named operator will reclaim the site according to the provisions of WV Code 22-6-30. Please be advised that form WR-38, Affidavit of Plugging and Filling Well, is to be submitted to this office within 90 days of completion of permitted well work, as should form WR-34 Discharge Monitoring Report within 30 days of discharge of pits, if applicable. Failure to abide by all statutory and regulatory provisions governing all duties and operations hereunder may result in suspension or revocation of this permit and, in addition, may result in civil and/or criminal penalties being imposed upon the operators.

Per 35 CSR 4-5.2.g this permit will expire in two (2) years from the issue date unless permitted well work is commenced. If there are any questions, please feel free to contact me at (304) 926- 0450.

James A. Martin  
Chief

A handwritten signature in blue ink, appearing to read "James A. Martin", is written over a faint, larger blue outline of the signature.

Operator's Well Number:  
Farm Name: BAKER, LOIS ANN  
U.S. WELL NUMBER: 47-091-01068-00-00  
Vertical Plugging  
Date Issued: 6/11/2025

# PERMIT CONDITIONS

West Virginia Code §22-6-11 allows the Office of Oil and Gas to place specific conditions upon this permit. Permit conditions have the same effect as law. Failure to adhere to the specified permit conditions may result in enforcement action.

## CONDITIONS

1. All pits must be lined with a minimum of 20 mil thickness synthetic liner.
2. In the event of an accident or explosion causing loss of life or serious personal injury in or about the well or while working on the well, the well operator or its contractor shall give notice, stating the particulars of the accident or explosion, to the oil and gas inspector and the Chief within twenty-four (24) hours.
3. Well work activities shall not constitute a hazard to the safety of persons.
4. Notification shall be given by the operator to the Oil and Gas Inspector at least 24 hours prior to the construction of roads, locations and/or pits for any permitted work. In addition, the well operator shall notify the same inspector 24 hours before any actual well work is commenced and prior to running and cementing casing.

1) Date May 30, 2025  
2) Operator's  
Well No. Baker #2  
3) API Well No. 47- 91 - 01088

STATE OF WEST VIRGINIA  
DEPARTMENT OF ENVIRONMENTAL PROTECTION  
OFFICE OF OIL AND GAS

APPLICATION FOR A PERMIT TO PLUG AND ABANDON

- 4) Well Type: Oil \_\_\_\_ / Gas \_\_\_\_ / Liquid injection \_\_\_\_ / Waste disposal \_\_\_\_ /  
(If "Gas, Production \_\_\_\_ or Underground storage \_\_\_\_) Deep \_\_\_\_ / Shallow X
- 5) Location: Elevation 1515' Watershed Tributary of Sandy Creek  
District Knottsville County Taylor Quadrangle Thornton (638)
- 6) Well Operator Diversified Production LLC 7) Designated Agent Chris Veazey  
Address 414 Summer Street Address 414 Summer Street  
Charleston, WV 25301 Charleston, WV 25301
- 8) Oil and Gas Inspector to be notified 9) Plugging Contractor  
Name Gayne Knitowski Name Coastal Drilling East, LLC  
Address 21 Energy Way Address 130 Meadows Ridge Road  
Gorman, WV 26720 Mt. Morris, PA 15349

- 10) Work Order: The work order for the manner of plugging this well is as follows:  
See Exhibit Nos. 1 and 2 and MSHA 101-C Exemption

ICG Tygart Valley, LLC (47-091-01089)

Leer Mine (MSHA ID# 46-09192)

MSHA 101-C Docket No. M-2012-065-C

Appropriate coal seam top = 351.35'

Approximate coal seam bottom = 358.26'

RECEIVED  
Office of Oil and Gas  
JUN 09 2025  
WV Department of  
Environmental Protection

Notification must be given to the district oil and gas inspector 24 hours before permitted work can commence.

Work order approved by inspector Gayne Knitowski Date 6-6-2025  
Digitally signed by Gayne Knitowski  
Date: 2025.06.06 07:39:23 -0400

06/13/2025

---

EXHIBIT NO. 1

---

From the experience and technology developed since 1970 in plugging oil and gas wells for mining through, Diversified Production will utilize the following method to plug all future wells.

**SOLID PLUG METHOD**

- a) If active well: clean out to total depth and plug back according to state regulations to a minimum of 200 feet below lowest minable coal seam.
- b) If abandoned well: clean out to first plug 200 feet below lowest minable coal seam.
- c) Circulate through tubing or drill steel an expanding cement plug from a minimum of 200 feet below minable coal seam to a point 100 feet above minable coal.

Circulate through tubing or drill steel from 100 feet above coal seam to surface.

A monument will be installed with API No. and stating "solid plug".

Gayne  
Knitowski

Digitally signed by  
Gayne Knitowski  
Date: 2025.06.06  
07:39:01 -04'00'

RECEIVED  
Office of Oil and Gas  
JUN 09 2025  
WV Department of  
Environmental Protection

06/13/2025



## EXHIBIT No. 2

Coastal Well Services, LLC • 130 Meadow Ridge Road, Mt. Morris, PA 15349

Phone 304-296-1120 Fax 304-413-0061

"A Shaft Drillers International Company"

Mr. Chuck Duckworth on behalf of Diversified Production LLC

Gas Well & Property Manager

Core Natural Resources

Arch Land LLC

100 Tygart Drive

Grafton, WV 26354

Mr. Duckworth,

Below is the proposed plugging plan we discussed that can be used on wells like the wells we have been plugging for the last few years. This is the procedure we will generally utilize to plug 47-091-01068, 01153, 01161, and 01233.

### Plugging Plan

- Move to site, rig up, mix mud, drill rathole
- Bullhead well and maintain static well head pressures
- Removed any/all of the 1 ½" tubing from surface to TD (5760')
- Clean out well to original total depth (5760').
- Run cement bond log on 4 ½" casing to determine top of cement
- Set bottom hole cement plug as required by the WV DEP from TD to top of cement determined by the bond log.
- Tag top of bottom hole plug to insure plug is at correct depth. Re-cement if necessary.
- Cut and pull 4 ½" casing from the free point determined by the bond log.
- Clean out wellbore to top of remaining 4 ½" casing
- Run suite of logs to determine casing size, bottom of casing, depth of coal seams, deviation of wellbore and cement bond to casing.
- Cement hole from top of bottom hole plug to a depth within 50' of the bottom of the 7" casing.
- If necessary cut and pull any free casing.
- Perforate, cut, rip or mill any remaining casing at depths determined by MSHA's 101C Petition for the Leer Mine.
- Multiple cuts may be required to be placed with both the bonded 7" and 9 5/8" casing strings. The cuts will be placed in 18" increments through the mining area in the Lower Kittanning Coal Seam.
- Cement hole from top of intermediate plug to surface using cement required by MSHA's 101C Petition for the Leer Mine.
- Rig down and set monument as required by WV DEP.
- Contractor will use Class A cement.

RECEIVED  
Office of Oil and Gas

JUN 09 2025

WV Department of  
Environmental Protection

Gayne  
Knitowski

Digitally signed by  
Gayne Knitowski  
Date: 2025.06.06  
07:39:54 -04'00'

06/13/2025



free area will be available. The free base will be located near the working face.

(5) Sufficient supplies of roof support and ventilation materials will be available and located near the working face. In addition, an emergency plug and/or plugs will be available within the immediate area of the well intersection.

(6) Equipment involved in mining through the well will be checked for permissibility and serviced on the maintenance shift prior to mining through the well. The methane monitor on the continuous mining machine involved in mining through the well will also be calibrated on the maintenance shift prior to mining through the well.

(7) When mining is in progress, tests for methane will be made with a handheld methane detector at least every 10 minutes, from the time that mining with the continuous mining machine is within 30 feet of the well until the well is intersected, and immediately prior to mining through. During the actual cutting-through process, no individual will be allowed on the return side until mining-through has been completed and the area has been examined and declared safe.

(8) The working area will be free from accumulations of coal dust and coal spillages, and rock dust will be placed on the roof, rib, and floor to within 30 feet of the face when mining through the well.

(9) When the well is intersected, all equipment will be deenergized and the place thoroughly examined and determined safe before mining is resumed.

(10) Any casing will be removed and no open flame will be permitted in the area until adequate ventilation has been established around the well.

(11) After a well has been intersected and the working place determined safe, mining will continue in by the well at a distance sufficient to permit adequate ventilation around the area of the well.

(12) No person will be permitted in the area of the mining-through operation except those actually engaged in the operation, company personnel, personnel from MSHA, and personnel from the Kentucky OMSL.

(13) The mining-through operation will be under the direct supervision of a certified individual. Instructions concerning the mining-through operation will be issued only by the certified individual in charge. MSHA personnel may interrupt or halt the mining through operation when necessary for the safety of the miners.

(14) Within 30 days after this Order becomes final, the petitioner will submit

proposed revisions for its approved mine emergency evacuation and firefighting plan required by 30 CFR 75.1501. The petitioner will revise the plans to include the hazards and evacuation procedures to be used for well intersections.

The petitioner further states that this petition will apply to all types of mining (conventional, continuous, and longwall) and asserts that the proposed alternative method will at all times provide a measure of protection no less than that of the existing standard.

*Docket Number:* M-2012-054-C.  
*Petitioner:* Lone Mountain Processing, Inc., Drawer C, St. Charles, Virginia 24282.

*Mine:* Mine No. 1, MSHA I.D. No. 15-16784, Route 836 Benedict Road, St. Charles, Virginia 24202, located in Floyd County, Kentucky.

*Regulation Affected:* 30 CFR 75.208 (Warning devices).

**Modification Request:** This petitioner requests a modification of the existing standard to permit a readily visible warning to be posted at the second row of permanent roof support on any unsupported roof or a physical barrier to be installed to impede travel beyond permanent support, except during the installation of roof supports. The petitioner states that:

(1) The Kentucky Office of Mine Safety and Licensing requires "a warning device to be installed on the second row of permanent roof support on any unsupported roof."

(2) MSHA's approved Regulations for Remote Control Operation of Continuous Mining Machines states that "While using remote controls, the continuous mining machine operator and all other persons will position themselves no closer than the second 'full row' of installed roof bolts on the face."

(3) This petition is necessary to improve safety and to attain compatibility between State and Federal regulations.

(4) Safety increases when the distance an employee keeps from unsupported roof increases.

The petitioner asserts that the proposed alternative method will at all times guarantee no less than the same measure of protection afforded by the existing standard.

*Docket Number:* M-2012-055-C.  
*Petitioner:* ICG Tygart Valley, LLC, 1200 Tygart Drive, Garon, West Virginia 26354.

*Mine:* Tygart #1 Mine, MSHA I.D. No. 46-09392, located in Taylor County, West Virginia.

*Regulation Affected:* 30 CFR 75.1700 (Oil and gas wells).

**Modification Request:** The petitioner requests a modification of the existing standard requiring that barriers be established and maintained around oil and gas wells penetrating canyons or underground areas of coal mines to permit an alternative method of compliance. The petitioner states that:

(1) The mine is projected to encounter vertical in-seam boreholes, typical of oil and natural gas wells, as mine development progresses.

(2) The active development section is approaching these boreholes, and is projected to encounter additional boreholes in the future as mining operations continue.

(3) The procedure presented in this petition will be used to ensure that mining through these boreholes is accomplished safely and, as an alternative to compliance with 30 CFR 75.1700, will provide no less than the same measure of protection to the miners, as required by the MSHA standard.

The petitioner proposes to use the following procedures when plugging oil or gas wells:

(1) Prior to plugging an oil or gas well, a diligent effort will be made to clean the borehole to the original total depth. If this depth cannot be reached, the borehole will be cleaned out to a depth that would permit the placement of at least 200 feet of expanding cement below the base of the lowest mineable coal bed.

(2) When cleaning the borehole, a diligent effort will be made to remove all of the casing in the borehole. If it is not possible to remove all of the casing, the casing that remains will be perforated or ripped at intervals spaced close enough to permit expanding cement slurry to infiltrate the annulus between the casing and the borehole wall for a distance of at least 200 feet below the base of the lowest mineable coal bed.

(3) If the cleaned-out borehole produces gas, a mechanical bridge plug will be placed in the borehole in a competent stratum at least 200 feet below the base of the lowest mineable coal bed, but above the top of the uppermost hydrocarbon-producing stratum. If it is not possible to set a mechanical bridge plug, a substantial brush plug may be used in its place.

The District Manager may allow the use of other effective methods of stopping any and all gas flow emitting from the wellbore before placement of cement through the mineable coal seam(s). Such approval will be documented in a written response to the operators' submittal of a detailed explanation of the method to be used.

RECEIVED  
Office of Oil and Gas

JUN 09 2025

WV Department of  
Environmental Protection

RECEIVED  
Office of Oil and Gas

AUG 30 2024

WV Department of  
Environmental Protection



and an engineering evaluation of the relative effectiveness of the alternative.

(4) A suite of logs will be made, consisting of a caliper survey, directional deviation survey, and log(s) suitable for determining the top and bottom of the lowest minable coal bed and potential hydrocarbon-producing strata and the location for the bridge plug.

(5) If the uppermost hydrocarbon-producing stratum is within 200 feet of the base of the lowest minable coal bed, properly placed mechanical bridge plugs or a suitable brush plug described in paragraph (2) above will be used to isolate the hydrocarbon-producing stratum from the expanding cement plug. Nevertheless, a minimum of 200 feet of expanding cement will be placed below the lowest minable coal bed.

(6) The wellbore will be completely filled and circulated with a gel that inhibits any flow of gas, supports the walls of the borehole, and increases the density of the expanding cement. This gel will be pumped through open-end tubing run to a point approximately 20 feet above the bottom of the cleaned out area of the borehole or bridge plug.

The petitioner proposes to use the following procedures when plugging gas and oil wells to the surface:

(1) A cement plug will be set in the wellbore by pumping expanding cement slurry down the tubing to displace the gel and fill the borehole to the surface. As an alternative, the cement slurry may be pumped down the tubing so that the borehole is filled. There will be at least 200 feet of expanding cement below the base of the lowest minable coal bed.

(2) A marker conforming to the requirements of the state regulatory authority will be installed at the borehole, or a small quantity of steel turnings or other small magnetic particles will be embedded in the top of the cement near the surface. The method used will be suitable to serve as a permanent magnetic monument of the borehole.

The following procedures will be used for the vent pipe method for plugging oil and gas wells:

(1) A 4 1/2-inch or larger pipe will be run into the wellbore to a depth of 100 feet below the lowest minable coal bed and wedged to a smaller diameter pipe that, if desired, will extend to a point approximately 20 feet above the bottom of the cleaned-out area of the borehole or bridge plug.

(2) A cement plug will be set in the wellbore by pumping expanding cement slurry, Portland cement, or a Portland cement-fly ash mixture down the tubing to displace the gel so that the borehole is filled with cement. The borehole and

the vent pipe will be filled with expanding cement for a minimum of 200 feet below the base of the lowest minable coal bed. The top of the expanding cement will extend upward to a point approximately 100 feet above the top of the lowest minable coal bed.

(3) All fluid will be evacuated from the vent pipe to facilitate testing for gases. During the evacuation of fluid, the expanding cement will not be disturbed.

(4) The top of the vent pipe will be protected to prevent liquids or solids from entering the wellbore, but permit ready access to the full internal diameter of the vent pipe when necessary.

The petitioner proposes to use the following procedures when plugging oil or gas wells for subsequent use as degasification boreholes:

(1) A cement plug will be set in the wellbore by pumping expanding cement slurry down the tubing to displace the gel and provide at least 200 feet of expanding cement below the lowest minable coal bed. The top of the expanding cement will extend upward to a point above the top of the coal bed being mined. This distance will be based on the average height of the coal strata breakage for the mine.

(2) To facilitate methane drainage, degasification casing of suitable diameter, slotted or perforated throughout the lower 160 to 200 feet, will be set in the borehole to a point 10 to 30 feet above the top of the expanding cement.

(3) The annulus between the degasification casing and the borehole wall will be cemented from a point immediately above the slots or perforations to the surface.

(4) The degasification casing will be cleaned out for its total length.

(5) The top of the degasification casing will be fitted with a wellhead equipped as required by the District Manager. Such equipment may include check valves, shut-in valves, sampling port, flame arrester equipment, and security fencing.

The following alternative procedures for preparing and plugging oil and gas wells will apply to wells that the petitioner and the District Manager agree cannot be completely cleaned out due to damage to the wall caused by subsidence, caving, or other factors; as determined by the petitioner and agreed to by the District Manager. These provisions will apply unless alternative measures are agreed upon and based upon a plan submitted to the District Manager:

(1) The petitioner will drill a hole adjacent and parallel to the well to a

depth of at least 200 feet below the lowest minable coal seam.

(2) The petitioner will use a geophysical sensing device to locate any casing that may remain in the wall.

(3) If the well contains casing(s), the petitioner will drill into the wall from the parallel hole. From 10 feet below the coal seam to 10 feet above the coal seam, the petitioner will perforate or rip all casings at intervals of at least 6 feet. Beyond this distance, the petitioner will perforate or rip at least every 50 feet from at least 200 feet below the base of the lowest minable coal seam up to 100 feet above the seam being mined. The petitioner will fill the annulus between the casing, and between the casings and the well wall with expanding cement (minimum 0.5 percent expansion upon setting), and will ensure that there are no voids. If the petitioner, using a casing bond log, can demonstrate to the satisfaction of the District Manager that the annulus of the well is adequately sealed with cement, then the petitioner will not be required to perforate or rip the casing for that particular well or fill these areas with cement. When multiple casing and tubing strings are present in the coal horizon(s), any casing that remains will be ripped or perforated and filled with expanding cement as indicated above. An acceptable casing bond log for each casing and tubing string is needed if used in lieu of ripping or perforating multiple strings.

(4) Where the petitioner determines and the District Manager agrees that there is insufficient casing in the well to allow the method outlined in paragraph (3) above to be used, then the petitioner will use a horizontal hydraulic

fracturing technique to intercept the original wall. From at least 200 feet below the base of the lowest minable coal seam to a point at least 50 feet above the seam being mined, the petitioner will fracture at least six places at intervals to be agreed upon by the petitioner and the District Manager after considering the geological strata and the pressure within the well. The petitioner will then pump expanding cement into the fractured well in sufficient quantities and in a manner that fills all intercepted voids.

(5) The petitioner will prepare down-hole logs for each well. The logs will consist of a caliper survey and log(s) suitable for determining the top, bottom, and thickness of all coal seams and potential hydrocarbon-producing strata and the location for the bridge plug. The petitioner may obtain the logs from the adjacent hole rather than the well if the condition of the well makes it impractical to insert the equipment

RECEIVED  
Office of Oil and Gas

JUN 09 2025

WV Department of  
Environmental Protection

RECEIVED  
Office of Oil and Gas

AUG 30 2024

WV Department of  
Environmental Protection



necessary to obtain the log. The District Manager may approve the use of a down-hole camera survey in lieu of down-hole logs if, in his or her judgment, such logs would not be suitable for obtaining the data or are impractical to obtain due to the condition of the drill hole. A journal will be maintained describing the length and type material used to plug the well; the length of casing(s) removed, perforated, or ripped or left in place; and other pertinent information concerning sealing the well.

(6) After the petitioner has plugged the well, the petitioner will plug the open portions of both holes from the bottom to the surface with Portland cement or a lightweight cement mixture. The petitioner will embed steel washers or other small magnetic particles in the top of the cement near the surface to serve as a permanent magnetic monument of the well. In the alternative, a 4½-inch or larger casing set in cement will extend at least 36 inches above the ground level. A combination of the methods outlined in paragraph (3) and (4) above may have to be used in a single well, depending upon the conditions of the hole and the presence of casings. The petitioner and the District Manager may discuss the nature of each hole and the District Manager may require the use of more than one method.

The petitioner proposes to use the following cut-through procedures whenever the safety barrier diameter is reduced to a distance less than the District Manager would approve pursuant to § 75.1700 or the petitioner proceeds with an intent to cut through a plugged well:

(1) Prior to reducing the safety barrier to a distance less than the District Manager would approve or proceeding with intent to cut through a plugged well, the petitioner will notify the District Manager.

(2) Mining in close proximity to or through a plugged well will be done on a shift approved by the District Manager.

(3) The District Manager, a representative of the miners, and the appropriate State agency will be notified by the operator in sufficient time prior to the mining-through operation to provide an opportunity for them to have a representative present.

(4) When using continuous mining equipment, driveage sights will be installed at the last open crosscut near the place to be sealed to ensure intersection of the well. The driveage sights will not be more than 60 feet from the well. When using longwall mining methods, driveage sights will be installed

on 10-foot centers for a distance of 50 feet in advance of the well jaws. The driveage sights will be installed in the headgate and tailgate.

(5) Firefighting equipment, including fire extinguishers, rock dust, and sufficient fire hose to reach the working face area of the mining-through will be available when either the conventional or continuous mining method is used. The fire hose will be located to the last open crosscut of the entry or room. All fire hoses will be ready for operation during the mining-through.

(6) Sufficient supplies of roof support and ventilation materials will be available and located at the last open crosscut. In addition, an emergency plug and/or plugs will be available in the immediate area of the cut-through.

(7) The quantity of air required by the approved mine ventilation plan, but not less than 6,000 cubic feet per minute (cfm) of air for scrubber-equipped continuous miners or not less than 9,000 cfm for continuous miner sections using auxiliary fans or line brattice only, will be used to ventilate the working face during the mining-through operation. The quantity of air required by the ventilation plan, but not less than 30,000 cfm, will reach the working face of each longwall during the mining-through operation.

(8) Equipment will be checked for permissibility and serviced on the shift prior to mining-through the well. The methane monitors on the continuous mining machine or the longwall shear and slice will be calibrated on the shift prior to mining through the well.

(9) When mining is in progress, tests for methane will be made with a hand-held methane detector at least every 10 minutes from the time that mining with the continuous mining machine is within 30 feet of the well until the well is intersected and immediately prior to mining through. When mining with longwall mining equipment, tests for methane will be made at least every 10 minutes when the longwall face is within 10 feet of the well. During the actual cutting-through process, no individual will be allowed on the return side until mining through has been completed and the area has been examined and declared safe.

(10) When using continuous mining methods, the working area will be free from accumulations of coal dust and coal spillages, and rock dust will be placed on the roof, rib, and floor to within 20 feet of the face when mining through or near the well on the shift or shifts during which the cut-through will occur. On longwall sections, rock-dusting will be conducted and placed

on the roof, rib, and floor up to both headgate and tailgate gob.

(11) When the wellbore is intersected, all equipment will be demagnetized and the area thoroughly examined and determined safe before mining is resumed. Any well casing will be removed and no open flame will be permitted in the area until adequate ventilation has been established around the wellbore.

(12) After a well has been intersected and the working area determined safe, mining will continue in by the well at a distance sufficient to permit adequate ventilation around the area of the wellbore.

(13) No person will be permitted in the area of the mining-through operation except those actually engaged in the operation, company personnel, representatives of the miners, personnel from MSHA, and personnel from the appropriate State agency.

(14) The mining-through operation will be under the direct supervision of a certified official. Instructions concerning the mining-through operation will be issued only by the certified official in charge. MSHA personnel may interrupt or halt the mining-through operation when necessary for the safety of the miners.

(15) The petitioner will file a plugging affidavit setting forth the persons who participated in the work, a description of the plugging work, and a certification by the petitioner that the well has been plugged as described.

(16) Within 60 days after the Proposed Decision and Order (PDO) becomes final, the petitioner will submit proposed revisions for its approved 30 CFR Part 40 training plan to the District Manager. The provisions will include initial and refresher training regarding compliance with the terms and conditions stated in the PDO.

The petitioner asserts that the proposed alternative method will at all times guarantee miners no less than the same measure of protection as afforded by the existing standard.

Docket Number: M-2012-002-M.  
Petitioner: Hecla Greens Creek Mining Company, P.O. Box 32190, Juneau, Alaska 99803.

Mine: Greens Creek Mine, MSHA No. 50-01267, located in Juneau County, Alaska.

Regulation Affected: 30 CFR 57.24180 (Roll-over protective structures (ROPS) and seat belts for surface equipment).

Modification Request: The petitioner requests a modification of the existing standard to permit employees to be transported 1,600 feet to and from the surface dry facility to work sites underground using underground mine

RECEIVED  
Office of Oil and Gas

JUN 09 2025

WV Department of  
Environmental Protection  
RECEIVED  
Office of Oil and Gas

AUG 30 2024

WV Department of  
Environmental Protection



State of West Virginia  
Department of Environmental Protection  
Office of Oil and Gas

Well Operator's Report of Well Work


Farm name: Lois Baker Operator Well No.: 2

LOCATION: Elevation: 1515' Quadangle: Thornton

District: Knottsville County: Taylor  
Latitude: 8170 Feet South of 39 Deg. 20 Min. 00 Sec.  
Longitude: 8640 Feet West of 79 Deg. 52 Min. 30 Sec.

Company: Texas Keystone, Inc.

	Casing & Tubing	Used in drilling	Left in well	Cement fill up Cu. Ft.
Address: 560 Epsilon Drive Pittsburgh PA, 15238				
Agent: Jon Farmer	13 3/8"	44.6'	44.6'	Sanded In
Inspector: Bill Hatfield				
Date Permit Issued: 7/13/2006	9 5/8"	364.5'	364.5'	120 SKS
Date Well Work Commenced: 11/13/06				
Date Well Work Completed: 11/17/06	7"	1174.5'	1174.5'	170 SKS
Verbal Plugging:				
Date Permission granted on: N/A	4 1/2"	5356'	5356'	235 SKS
Rotary X Cable Rlg				
Total Depth (feet): 5436'				
Fresh Water Depth (ft.): 415'				
Salt Water Depth (ft.):				
Is coal being mined in area (N/Y)? N				
Coal Depths (ft.): 205', 365', 400'				



OPEN FLOW DATA

Producing formation 3<sup>rd</sup> Elk Pay zone depth (ft) 5303' - 5306'  
Gas: Initial open flow G/S TSTM MCF/d Oil: Initial open flow 0 Bbl/d  
Final open flow still testing MCF/d Oil: Final open flow 0 Bbl/d  
Time of open flow between initial and final tests NA Hours  
Static rock Pressure not recorded psig (surface pressure) after N/A Hours

Second Producing formation 3<sup>rd</sup> Elk A Pay zone depth (ft) 5245' - 5248'  
Gas: Initial open flow Co-mingled MCF/d Oil: Initial open flow 0 Bbl/d  
Final open flow Co-mingled MCF/d Oil: Final open flow 0 Bbl/d  
Time of open flow between initial and final tests NA Hours  
Static rock Pressure Co-mingled psig (surface pressure) after        Hours

Third Producing formation 3<sup>rd</sup> Elk Pay zone depth (ft) 5115' - 5125'  
Gas: Initial open flow Co-mingled MCF/d Oil: Initial open flow 0 Bbl/d  
Final open flow Co-mingled MCF/d Oil: Final open flow 0 Bbl/d  
Time of open flow between initial and final tests NA Hours  
Static rock Pressure Co-mingled psig (surface pressure) after        Hours

Fourth Producing formation 3<sup>rd</sup> Riley Pay zone depth (ft) 4026' - 4030'  
Gas: Initial open flow Co-mingled MCF/d Oil: Initial open flow 0 Bbl/d  
Final open flow Co-mingled MCF/d Oil: Final open flow 0 Bbl/d  
Time of open flow between initial and final tests NA Hours  
Static rock Pressure Co-mingled psig (surface pressure) after        Hours

Fifth Producing formation Balltown A & B Pay zone depth (ft) 2934' - 3026'  
Gas: Initial open flow Co-mingled MCF/d Oil: Initial open flow 0 Bbl/d  
Final open flow Co-mingled MCF/d Oil: Final open flow 0 Bbl/d  
Time of open flow between initial and final tests NA Hours  
Static rock Pressure Co-mingled psig (surface pressure) after        Hours

NOTE: ON BACK OF THIS FORM PUT THE FOLLOWING: 1). DETAILS OF PERFORATED INTERVALS, FRACTURING OR STIMULATING, PHYSICAL CHANGE, ETC. 2). THE WELL LOG WHICH IS A SYSTEMATIC DETAILED GEOLOGICAL RECORD OF ALL FORMATIONS, INCLUDING COAL ENCOUNTERED BY THE WELLBORE.

Signed: [Signature]  
By: PAUL M. HERZOG  
Date: 2-19-07

RECEIVED  
Office of Oil and Gas  
JUN 09 2025  
WV Department of  
Environmental Protection

06/13/2025

2/16/07

Perfed 3<sup>rd</sup> Elk 5245' - 5248' (6 shots), 3<sup>rd</sup> Elk A 5303' - 5306' (6 shots). BD 3143#. 275 sks 20/40.434,000 scf N<sub>2</sub> - Foam Frac.Perfed 3<sup>rd</sup> Elk 5115' - 5118' (9 shots), 5123' - 5125' (6 shots). BD 4237#. 290 sks 20/40. 361,000 scf N<sub>2</sub> - Foam Frac.Perfed 3<sup>rd</sup> Riley 4026' - 4030' (12 shots). BD 3485#. 200 sks 20/40. 275,000 scf N<sub>2</sub> - Foam Frac.

Perfed Balltown A &amp; B 2934' - 2940' (12 shots), 3006' - 3009' (6 shots), 3012' - 3014' (4 shots), 3024' - 3026' (4 shots).

BD 1845#. 400 sks 20/40. 517,105 scf N<sub>2</sub> - Foam Frac.

ROCK DESCRIPTION	TOP DEPTH	BOTTOM DEPTH	NOTES
LET DOWN	0	7	
FILL	7	9	
SHALE	9	30	
SANDSTONE	30	95	
SHALE	95	195	
SANDSTONE	195	205	
COAL	205	207	
SHALE	207	240	
SANDSTONE	240	310	
SHALE	310	365	
COAL	365	377	
SHALE	377	400	
COAL	400	407	
SHALE	407	410	
SANDY SHALE	410	435	1/2" FW @ 415'
SANDSTONE	435	485	
SHALE	485	490	
SANDSTONE	490	635	
SANDY SHALE	635	650	
SHALE	650	715	
SANDY SHALE	715	725	
SANDSTONE	725	800	
SHALE	800	867	
SANDSTONE	867	930	
SANDY SHALE	930	960	
SANDSTONE	960	995	
RED ROCK	995	1020	
SHALE	1020	1109	
LITTLE LIME	1109	1124	
PENCIL CAVE SHALE	1124	1148	
BIG LIME	1148	1360	
SHALE	1360	1378	
SANDY SHALE	1378	1388	
SANDSTONE	1388	1398	
SANDY SHALE	1398	1448	
WEIR SANDSTONE	1448	1486	
SANDY SHALE	1486	1634	
QUANTZ SANDSTONE	1634	1664	
SHALE	1664	1678	
SANDSTONE	1678	1720	
SANDY SHALE	1720	2146	
UPPER 4 <sup>TH</sup> SAND	2146	2168	
SHALE	2168	2208	
SANDY SHALE	2208	2336	
BAYARD SANDSTONE	2336	2362	
SHALE	2362	2402	
SPEECHLEY A SANDSTONE	2402	2429	
SHALE	2429	2482	
SPEECHLEY B SANDSTONE	2482	2488	
SHALE	2488	2515	
SANDY SHALE	2515	2542	
SHALE	2542	2930	
BALLTOWN A SANDSTONE	2930	2971	
SHALE	2971	3004	
BALLTOWN B SANDSTONE	3004	3030	
SHALE	3030	3155	
SANDY SHALE	3155	3180	
SHALE	3180	4024	
3 <sup>RD</sup> RILEY SANDSTONE	4024	4038	
SANDY SHALE	4038	4090	
SHALE	4090	4190	
SANDY SHALE	4190	4325	
SHALE	4325	4397	
SANDY SHALE	4397	4455	
SHALE	4455	4834	
2 <sup>ND</sup> ELK SANDSTONE	4834	4860	
SANDY SHALE	4860	4932	
2 <sup>ND</sup> ELK A SANDSTONE	4932	4938	
SANDY SHALE	4938	5098	
3 <sup>RD</sup> ELK SANDSTONE	5098	5148	GAS SHOW @ 5115' TSTM
SANDY SHALE	5148	5236	
3 <sup>RD</sup> ELK A SANDSTONE	5236	5250	GAS SHOW @ 5245' TSTM
SHALE	5250	5299	
3 <sup>RD</sup> ELK SANDSTONE	5299	5344	GAS SHOW @ 5306' TSTM
SHALE	5344	5436	TD

RECEIVED  
Office of Oil and Gas

JUN 09 2025

WV Department of  
Environmental Protection

06/13/2025



WW-4A  
Revised 6-07

1) Date: May 30, 2025  
2) Operator's Well Number  
Baker #2

3) API Well No.: 47 - 91 - 01068

STATE OF WEST VIRGINIA  
DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS  
NOTICE OF APPLICATION TO PLUG AND ABANDON A WELL


4) Surface Owner(s) to be served:	5) (a) Coal Operator
(a) Name <u>Bradley Dean Baker and Craig Monroe Baker</u>	Name <u>CoalQuest Development, LLC</u>
Address <u>197 Thomas Farm Road</u>	Address <u>100 Tygart Drive</u>
<u>Thomton, West Virginia 26440</u>	<u>Grafton, West Virginia 26354</u>
(b) Name _____	(b) Coal Owner(s) with Declaration
Address _____	Name _____
	Address _____
(c) Name _____	Name _____
Address _____	Address _____
6) Inspector <u>Gayne Knitowski</u>	(c) Coal Lessee with Declaration
Address <u>21 Energy Way</u>	Name _____
<u>Gorman, WV 26720</u>	Address _____
Telephone <u>(304) 546-8171</u>	

TO THE PERSONS NAMED ABOVE: You should have received this Form and the following documents:

- (1) The application to Plug and Abandon a Well on Form WW-4B, which sets out the parties involved in the work and describes the well its and the plugging work order; and
- (2) The plat (surveyor's map) showing the well location on Form WW-6.

The reason you received these documents is that you have rights regarding the application which are summarized in the instructions on the reverses side. However, you are not required to take any action at all.

Take notice that under Chapter 22-6 of the West Virginia Code, the undersigned well operator proposes to file or has filed this Notice and Application and accompanying documents for a permit to plug and abandon a well with the Chief of the Office of Oil and Gas, West Virginia Department of Environmental Protection, with respect to the well at the location described on the attached Application and depicted on the attached Form WW-6. Copies of this Notice, the Application, and the plat have been mailed by registered or certified mail or delivered by hand to the person(s) named above (or by publication in certain circumstances) on or before the day of mailing or delivery to the Chief.



Well Operator Diversified Production LLC  
By: CHRIS VERLEY  
Its: [Signature]  
Address 414 Summer Street  
Charleston, West Virginia 25301  
Telephone (304) 543-8988

RECEIVED  
Office of Oil and Gas

Subscribed and sworn before me this 2nd day of June 2025  
Rebecca Wanstreet Notary Public  
My Commission Expires 7-26-2029

JUN 09 2025  
WV Department of  
Environmental Protection

Oil and Gas Privacy Notice

The Office of Oil and Gas processes your personal information, such as name, address and phone number, as a part of our regulatory duties. Your personal information may be disclosed to other State agencies or third parties in the normal course of business or as needed to comply with statutory or regulatory requirements, including Freedom of Information Act requests. Our office will appropriately secure your personal information. If you have any questions about our use of your personal information, please contact DEP's Chief Privacy Officer at [depprivacyofficer@wv.gov](mailto:depprivacyofficer@wv.gov).

06/13/2025

## SURFACE OWNER WAIVER

Operator's Well  
Number

Baker #2

### INSTRUCTIONS TO SURFACE OWNERS NAMED ON PAGE WW4-A

The well operator named on page WW-4A is applying for a permit from the State to plug and abandon a well. (Note: If the surface tract is owned by more than three persons, then these materials were served on you because your name appeared on the Sheriff's tax ticket on the land or because you actually occupy the surface tract. In either case, you may be the only owner who will actually receive these materials.) See Chapter 22 of the West Virginia Code. Well work permits are valid for 24 months. If you do not own any interest in the surface tract, please forward these materials to the true owner immediately if you know who it is. Also, please notify the well operator and the Office of Oil and Gas.

**NOTE: YOU ARE NOT REQUIRED TO FILE ANY COMMENT.**  
**WHERE TO FILE COMMENTS AND OBTAIN ADDITIONAL INFORMATION:**

Chief, Office of Oil and Gas  
Department of Environmental Protection  
601 57<sup>th</sup> St. SE  
Charleston, WV 25304  
(304) 926-0450

**Time Limits and methods for filing comments.** The law requires these materials to be served on or before the date the operator files his Application. You have **FIVE (5) DAYS** after the filing date to file your comments. Comments must be filed in person or received in the mail by the Chief's office by the time stated above. You may call the Chief's office to be sure of the date. Check with your postmaster to ensure adequate delivery time or to arrange special expedited handling. If you have been contacted by the well operator and you have signed a "voluntary statement of no objection" to the planned work described in these materials, then the permit may be issued at any time.

**Comments must be in writing.** Your comments must include your name, address and telephone number, the well operator's name and well number and the approximate location of the proposed well site including district and county from the application. You may add other documents, such as sketches, maps or photographs to support your comments.

The Chief has the power to deny or condition a well work permit based on comments on the following grounds:

- 1) The proposed well work will constitute a hazard to the safety of persons.
- 2) The soil erosion and sediment control plan is not adequate or effective;
- 3) Damage would occur to publicly owned lands or resources;
- 4) The proposed well work fails to protect fresh water sources or supplies;
- 5) The applicant has committed a substantial violation of a previous permit or a substantial violation of one or more of the rules promulgated under Chapter 22, and has failed to abate or seek review of the violation..."

RECEIVED  
Office of Oil and Gas

JUN 09 2025

WV Department of  
Environmental Protection

If you want a copy of the permit as it is issued or a copy of the order denying the permit, you should request a copy from the Chief.


### VOLUNTARY STATEMENT OF NO OBJECTION

I hereby state that I have read the instructions to surface owners and that I have received copies of a Notice and Application For A Permit To Plug And Abandon on Forms WW-4A and WW-4B, and a survey plat.

I further state that I have no objection to the planned work described in these materials, and I have no objection to a permit being issued on those materials.

FOR EXECUTION BY A NATURAL PERSON  
ETC.

FOR EXECUTION BY A CORPORATION,

 Date 6-4 Name \_\_\_\_\_  
Signature By \_\_\_\_\_  
Its \_\_\_\_\_ Date \_\_\_\_\_

Signature

Date  
**06/13/2025**



WW-4B

API No.	47-091-01068
Farm Name	Baker, Lois Ann
Well No.	Baker #2

## INSTRUCTIONS TO COAL OPERATORS OWNERS AND LESSEE

The well operator named on the obverse side of WW-4 (B) is about to abandon the well described in the enclosed materials and will commence the work of plugging and abandoning said well on the date the inspector is notified. Which date shall not be less than five days after the day on which this notice and application so mailed is received, or in due course should be received by the Department of Environmental Protection Office of Oil & Gas.


This notice and application is given to you in order that your respective representatives may be present at the plugging and filling of said well. You are further notified that whether you are represented or not the operator will proceed to plug and fill said well in the manner required by Section 24, Article 6, Chapter 22 of the Code and given in detail on obverse side of this application.

NOTE: If you wish this well to be plugged according to 22-6-24(d) then as per Regulation 35CSR4-13.9 you must complete and return to this office on form OB-16 "Request by Coal Operator, Owner, or Lessee for plugging" prior to the issuance of this plugging permit.

## WAIVER

The undersigned coal operator X / owner \_\_\_\_\_ / lessee \_\_\_\_\_ / of the coal under this well location has examined this proposed plugging work order. The undersigned has no objection to the work proposed to be done at this location, provided, the well operator has complied with all applicable requirements of the West Virginia Code and the governing regulations.

Date: 6/4/2025

CoalQuest Development, LLC  
By: Greg Nair   
Its Power of Attorney

RECEIVED  
Office of Oil and Gas  
JUN 09 2025  
WV Department of  
Environmental Protection

06/13/2025

**POWER OF ATTORNEY**

**COALQUEST DEVELOPMENT LLC  
TO  
GREG NAIR**

**Dated: January 1, 2025**

**Expires: December 31, 2025**


KNOW ALL MEN BY THESE PRESENTS: That CoalQuest Development LLC, a limited liability company formed under the laws of the State of Delaware (the "Company"), acting by and through Rosemary L. Klein, its duly authorized Secretary, has and does hereby appoint Greg Nair its true and lawful Attorney-in-Fact with power and authority, for and on behalf, and in the name of the Company, during the period herein specified, and subject to the restrictions and limitations set forth in this Power, to execute, acknowledge and deliver in the ordinary and regular course of the Company's business, applications for mining, environmental, safety, and health permits, permit transfers, or permit bond releases or bond adjustments, amendments, supplements or modifications to such permits, certificates, gas well plugging applications, shallow well drilling permit applications, or other instruments directly related to such amendments, supplements or modifications, monthly production reports, air quality, water quality or other environmental reports, quarterly discharge monitoring reports and any other like or similar reports required to be filed with any local, state or federal governmental agency.

The Attorney herein appointed shall be authorized to act pursuant to this Power from the date hereof only so long as such Attorney shall remain an employee of Arch Resources, Inc. or any subsidiary thereof, or until December 31, 2025, or until such earlier time as this instrument has been revoked, annulled, rescinded or set aside by an instrument of revocation filed with the Secretary of the Company, whichever first occurs.

IN WITNESS WHEREOF, the Company has caused this Power of Attorney to be executed on its behalf, and its seal to be hereunto affixed as of the day and year first above written, by the undersigned, Rosemary L. Klein, duly authorized Secretary of the Company.

COALQUEST DEVELOPMENT LLC

By: \_\_\_\_\_

  
Rosemary L. Klein  
Secretary

RECEIVED  
Office of Oil and Gas

JUN 09 2025

WV Department of  
Environmental Protection

06/13/2025




STATE OF MISSOURI     )  
                                      ) ss  
COUNTY OF ST. LOUIS    )

On this 13<sup>th</sup> day of December, 2024, before me, the undersigned notary public,  
personally appeared Rosemary L. Klein, known to me to be the person whose name is subscribed  
to the within instrument and acknowledged that she executed the same for the purposes therein  
contained.

IN WITNESS WHEREOF, I hereunto set my hand and official seal.

Angela Dabrosky  
Notary Public

My Commission Expires: NOV. 6, 2026



RECEIVED  
Office of Oil and Gas  
JUN 09 2025  
WV Department of  
Environmental Protection

06/13/2025

WW-9  
(5/16)

API Number 47 - 091 01068  
Operator's Well No. Baker #2

STATE OF WEST VIRGINIA  
DEPARTMENT OF ENVIRONMENTAL PROTECTION  
OFFICE OF OIL AND GAS  
FLUIDS/ CUTTINGS DISPOSAL & RECLAMATION PLAN

Operator Name Diversified Production LLC OP Code \_\_\_\_\_  
Watershed (HUC 10) Tributary of Sandy Creek Quadrangle Thomson (638)

Do you anticipate using more than 5,000 bbls of water to complete the proposed well work? Yes ☐ No ☒

Will a pit be used? Yes ☐ No ☒

If so, please describe anticipated pit waste: N/A

Will a synthetic liner be used in the pit? Yes ☐ No ☒ If so, what ml? \_\_\_\_\_

Proposed Disposal Method For Treated Pit Wastes:

- ☐ Land Application (if selected provide a completed form WW-9-GPP)
- ☐ Underground Injection ( UIC Permit Number \_\_\_\_\_ )
- ☐ Reuse (at API Number \_\_\_\_\_ )
- ☐ Off Site Disposal (Supply form WW-9 for disposal location)
- ☒ Other (Explain Tanks - See attached letter)

Will closed loop system be used? If so, describe: Yes, Gel circulated from tank thru well bore and returned to tank.

Drilling medium anticipated for this well (vertical and horizontal)? Air, freshwater, oil based, etc. freshwater

-If oil based, what type? Synthetic, petroleum, etc.

Additives to be used in drilling medium? Bentonite, Bicarbonate or Soda

Drill cuttings disposal method? Leave in pit, landfill, removed offsite, etc. removed offsite

-If left in pit and plan to solidify what medium will be used? (cement, lime, sawdust) \_\_\_\_\_

-Landfill or offsite name/permit number? ICG Tygart Valley, LLC - Permit No. O-2017-06

Permittee shall provide written notice to the Office of Oil and Gas of any load of drill cuttings or associated waste rejected at any West Virginia solid waste facility. The notice shall be provided within 24 hours of rejection and the permittee shall also disclose where it was properly disposed.

I certify that I understand and agree to the terms and conditions of the GENERAL WATER POLLUTION PERMIT issued on April 1, 2016, by the Office of Oil and Gas of the West Virginia Department of Environmental Protection. I understand that the provisions of the permit are enforceable by law. Violations of any term or condition of the general permit and/or other applicable law or regulation can lead to enforcement action.

I certify under penalty of law that I have personally examined and am familiar with the information submitted on this application form and all attachments thereto and that, based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine or imprisonment.

Company Official Signature [Signature]  
Company Official (Typed Name) CURIS VERZEY  
Company Official Title DIRECTOR OF ADMINISTRATION

RECEIVED  
Office of Oil and Gas

JUN 09 2025

WV Department of  
Environmental Protection

Subscribed and sworn before me this 2nd day of June, 2025

Rebecca Wandstreet

Notary Public

My commission expires 7-26-2029



OFFICIAL SEAL  
NOTARY PUBLIC  
STATE OF WEST VIRGINIA  
Rebecca Wandstreet  
104 Helport Loop Road  
Bridgeport, WV 26330  
My Commission Expires July 26, 2029



OFFICIAL SEAL  
NOTARY PUBLIC  
STATE OF WEST VIRGINIA  
Rebecca Wandstreet  
104 Helport Loop Road  
Bridgeport, WV 26330  
My Commission Expires July 26, 2029

06/13/2025

Proposed Revegetation Treatment: Acres Disturbed 1.50 / 2.0 Prevegetation pH \_\_\_\_\_Lime 3 Tons/acre or to correct to pH 6.5Fertilizer type 10-20-20 or equivalentFertilizer amount 500 lbs/acreMulch Hay Bales Tons/acreSeed Mixtures

Temporary		Permanent	
Seed Type	lbs/acre	Seed Type	lbs/acre
Orchard Grass	12	Orchard Grass	12
Landino Clover	3	Landino Clover	3
Timothy	10	Timothy	10

## Attach:

Maps(s) of road, location, pit and proposed area for land application (unless engineered plans including this info have been provided). If water from the pit will be land applied, provide water volume, include dimensions (L, W, D) of the pit, and dimensions (L, W), and area in acres, of the land application area.

Photocopied section of involved 7.5' topographic sheet.

 Plan Approved by: Gayne Knitowski Digitally signed by Gayne Knitowski Date: 2025.06.06 07:38:21 -0400

Comments: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

RECEIVED  
Office of Oil and Gas

JUN 09 2025

WV Department of  
Environmental ProtectionTitle: Inspector Date: 6-6-2025Field Reviewed? ( ☒ ) Yes ( ☐ ) No

06/13/2025



May 30, 2025


WV Department of Environmental Protection  
Office of Oil and Gas  
601 – 57<sup>th</sup> Street, S.E.  
Charleston, West Virginia 25304

To Whom It May Concern:

As per the WV Department of Environmental Protection, Office of Oil and Gas request, Diversified Production LLC, submits the following procedures utilizing pit waste.


Upon submitting a well work application (without a general permit for Oil and Gas Pit Waste Discharge Application), Diversified Production LLC, will construct no pits, but instead will use mud tanks to contain all drilling muds.

Once the well is completed, that material (minus the cave material) will be trucked to the next well to be plugged or to DEP impoundment facilities O-2017-06 or to an approved facility that can handle the material.

Sincerely,  
  
Chris Veazey

RECEIVED  
Office of Oil and Gas  
JUN 09 2025  
WV Department of  
Environmental Protection

06/13/2025



RECEIVED  
Office of Oil and Gas  
JUN 09 2025  
WV Department of  
Environmental Protection

06/13/2025







WW-7  
8-30-06



West Virginia Department of Environmental Protection  
Office of Oil and Gas  
**WELL LOCATION FORM: GPS**

API: 47-091-01068 WELL NO.: Baker #2  
FARM NAME: Baker, Lois Ann  
RESPONSIBLE PARTY NAME: Diversified Production LLC  
COUNTY: Taylor DISTRICT: Knottsville  
QUADRANGLE: Thornton  
SURFACE OWNER: Bradley Dean Baker and Craig Monroe Baker  
ROYALTY OWNER: Bradley Dean Baker and Craig Monroe Baker  
UTM GPS NORTHING: 4351859  
UTM GPS EASTING: 594364 GPS ELEVATION: 1519.01'

The Responsible Party named above has chosen to submit GPS coordinates in lieu of preparing a new well location plat for a plugging permit or assigned API number on the above well. The Office of Oil and Gas will not accept GPS coordinates that do not meet the following requirements:

1. Datum: NAD 1983, Zone: 17 North, Coordinate Units: meters, Altitude: height above mean sea level (MSL) – meters.
2. Accuracy to Datum – 3.05 meters
3. Data Collection Method:

Survey grade GPS x : Post Processed Differential \_\_\_\_\_

Real-Time Differential x \_\_\_\_\_

Mapping Grade GPS \_\_\_\_\_ : Post Processed Differential \_\_\_\_\_

Real-Time Differential \_\_\_\_\_

4. Letter size copy of the topography map showing the well location. **En**

I the undersigned, hereby certify this data is correct to the best of my knowledge and belief and shows all the information required by law and the regulations issued and prescribed by the Office of Oil and Gas.

Signature

DIRECTOR OF OIL AND GAS  
Title

6/2/2015  
Date

RECEIVED  
Office of Oil and Gas

JUN 09 2025

WV Department of  
Environmental Protection

06/13/2025



Dustin T. Kimble  
Land Agent  
P 304•265•9777  
E dustinkimble@coreresources.com

June 6, 2025

West Virginia Department of Environmental Protection  
Office of Oil and Gas  
601 57<sup>th</sup> Street, SE  
Charleston, WV 25304

Re: Gas Well Plugging Application

Gentlemen,

Enclosed, please find the plugging permit application for Gas Well 47-091-01068. This well is located inside the Leer Mine plan and will be plugged to MSHA and the WV Office of Mine Health, Safety and Training standards per Leer's approved 101-C petition.

Plugging of this well has become critical and will require plugging to commence shortly after permit issuance. Any expedition of the review and approval process would be greatly appreciated.

Please contact me if you have any questions or require anything further.

Sincerely,

A handwritten signature in blue ink that reads 'Dustin Kimble'.

Dustin Kimble

RECEIVED  
Office of Oil and Gas  
JUN 09 2025  
WV Department of  
Environmental Protection

06/13/2025



Kennedy, James P &lt;james.p.kennedy@wv.gov&gt;

---

**plugging permit issued 4709101068**

1 message

**Kennedy, James P** <james.p.kennedy@wv.gov>

Wed, Jun 11, 2025 at 9:35 AM

To: "Kimble, Dustin T." &lt;DustinKimble@coreresources.com&gt;, Gayne J Knitowski &lt;gayne.j.knitowski@wv.gov&gt;, ckinsey@wvassessor.com

To whom it may concern, a plugging permit has been issued for 4709101068.

--

***James Kennedy***

Environmental Resource Specialist III / Permitting

WVDEP Office of Oil and Gas

601 57<sup>th</sup> Street, SE

Charleston, WV 25304

304-926-0499 ext. 45025

[james.p.kennedy@wv.gov](mailto:james.p.kennedy@wv.gov)**4709101068.pdf**

3095K

06/13/2025