

west virginia department of environmental protection

Office of Oil and Gas 601 57th Street SE Charleston, WV 25304 (304) 926-0450 (304) 926-0452 fax Earl Ray Tomblin, Governor Randy C. Huffman, Cabinet Secretary www.dep.wv.gov

August 01, 2013

WELL WORK PERMIT

Horizontal 6A Well

This permit, API Well Number: 47-9703850, issued to CNX GAS COMPANY LLC , is evidence of permission granted to perform the specified well work at the location described on the attached pages and located on the attached plat, subject to the provisions of Chapter 22 of the West Virginia Code of 1931, as amended, and all rules and regulations promulgated thereunder, and to all conditions and provisions outlined in the pages attached hereto. Notification shall be given by the operator to the Oil and Gas Inspector at least 24 hours prior to the construction of roads, locations, and/or pits for any permitted work. In addition, the well operator shall notify the same inspector 24 hours before any actual well work is commenced and prior to running and cementing casing. Spills or emergency discharges must be promptly reported by the operator to 1-800-642-3074 and to the Oil and Gas inspector.

Please be advised that form WR-35, Well Operators Report of Well Work is to be submitted to this office within 90 days completion of permitted well work, as should form WR-34 Discharge Monitoring Report within 30 days of discharge of pits, if applicable. Failure to abide by all statutory and regulatory provisions governing all duties and operations hereunder may result in suspension or revocation of this permit and, in addition, may result in civil and/or criminal penalties being imposed upon the operators.

In addition to the applicable requirements of this permit, and the statutes and rules governing oil and gas activity in WV, this permit may contain specific conditions which must be followed. Permit conditions are attached to this cover letter.

Per 35CSR-4-5.2.g this permit will expire in two (2) years from the issue date unless permitted well work is commenced. If there are any questions, please feel free to contact me at (304) 926-0499 ext. 1654.

James Martin

Chie

Operator's Well No: CENT 19 DHS

Farm Name: ROHR, WILLIAM

API Well Number: 47-9703850 Permit Type: Horizontal 6A Well

Date Issued: 08/01/2013

PERMIT CONDITIONS

West Virginia Code § 22-6A-8(d) allows the Office of Oil and Gas to place specific conditions upon this permit. Permit conditions have the same effect as law. <u>Failure to adhere to the specified permit conditions may result in enforcement action.</u>

CONDITIONS

- 1. If the operator encounters an unanticipated void, or an anticipated void at an unanticipated depth, the operator shall notify the inspector within 24 hours. Modifications to the casing program may be necessary to comply with W. Va. Code § 22-6A-5a (12), which requires drilling to a minimum depth of thirty feet below the bottom of the void, and installing a minimum of twenty (20) feet of casing. Under no circumstance should the operator drill more than fifty (50) feet below the bottom of the void or install less than twenty (20) feet of casing below the bottom of the void.
- 2. When compacting fills, each lift before compaction shall not be more than 12 inches in height, and the fill material shall be within plus or minus 2% (unless soil test results show a greater range of moisture content is appropriate and 95% compaction can still be achieved) of the optimum moisture content as determined by the standard proctor density test, ASTM D698, Standard Test Method for Laboratory Compaction Characteristics of Soil Using Standard Effort. Each lift must meet 95% compaction of the optimum density based on results from the standard proctor density test of the actual soils used in specific engineered fill sites. Each lift shall be tested for compaction, with a minimum of two tests per lift per acre of fill. All test results shall be maintained on site and available for review.
- 3. Operator shall install signage per § 22-6A-8g (6) (B) at all source water locations included in their approved water management plan within 24 hours of water management plan activation.
- 4. Oil and gas water supply wells will be registered with the Office of Oil and Gas and all such wells will be constructed and plugged in accordance with the standards of the Bureau for Public Health set forth in its Legislative rule entitled *Water Well Regulations*, 64 C.S.R. 19. Operator is to contact the Bureau of Public Health regarding permit requirements. In lieu of plugging, the operator may transfer the well to the surface owner upon agreement of the parties. All drinking water wells within fifteen hundred feet of the water supply well shall be flow tested by the operator upon request of the drinking well owner prior to operating the water supply well.
- 5. Pursuant to the requirements pertaining to the sampling of domestic water supply wells/springs the operator shall, no later than thirty (30) days after receipt of analytical data provide a written copy to the Chief and any of the users who may have requested such analyses.
- 6. If any explosion or other accident causing loss of life or serious personal injury occurs in or about a well or well work on a well, the well operator or its contractor shall give notice, stating the particulars of the explosion or accident, to the oil and gas inspector and the Chief, within 24 hours of said accident.
- 7. During the casing and cementing process, in the event cement does not return to the surface, the oil and gas inspector shall be notified within 24 hours.

STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS W.VA. CODE §22-6A - WELL WORK PERMIT APPLICATION

					91	05	281
1) Well Operator:	CNX Gas	Company, LLC.		494458046	Upshur	Warren	Century
				Operator ID	County	District	Quadrangle
2) Operator's Well	Number	CENT19D	HS		Well Pad Na	те: СЕПТ19НЅ	
3 Elevation, curren	t ground	1582.60	b' El	evation, proposed	d post-constru	iction:	1585'
	Gas Other If Gas:	Shallow Horizonta	Oil	Deep			
5) Existing Pad? Yo	es or No	: No		=			
6) Proposed Target Formation - Marcellus, De				ed Thicknesses a	nd Associate	d Pressure(s):	
7) Proposed Total V	Vertical :	Depth:	8015'				
8) Formation at Tot	tal Verti	cal Depth:	Marcellus				
9) Proposed Total N	Measure	d Depth:	17250'				
10) Approximate F	resh Wa	ter Strata D	epths: 13	30', 550'			
11) Method to Dete	ermine F	resh Water	Depth: R	eference offset wells (API	#'s 47-097-00820 a	and 47-097-00556)	
12) Approximate S	altwater	Depths:	None Reported				
13) Approximate C	oal Sear	n Depths:	105', 550'				/
14) Approximate D	epth to	Possible Vo	id (coal mine,	karst, other):	None Anticipa	ated V	/
15) Does land conta	ain coal	seams tribu	tary or adjacer	nt to, active mine	? No		
16) Describe propo	sed well	work:	Drill and stimulate n	ew horizontal Marcellus w	rell. Well to be drille	d to a TMD of 17250'	. Well to be drilled to a
TVD of 8015', formation a	at TVD - Marc	ellus. If an unexp	ected void is encounte	red, plan will be to set casi	ng at a minimum of 3	80' past void and ceme	nt to surface with
approved Class A type ce	ement.						
	ultiple stages	divided over the la	ateral length of the wel	I. Stage spacing is depend	dent upon engineerin Rece		racturing technique will
be utilized on each stage	using sand,	water, and Gremic	ais.		Office of	Oil & Gas	
18) Total area to be	disturb	ed, includin	g roads, stocki	oile area, pits, etc	, (acres):	2013 25 Acres	
19) Area to be distu					16 Acres		

20)

CASING AND TUBING PROGRAM

TYPE	Size	New or Used	Grade	Weight per ft.	FOOTAGE: For Drilling	INTERVALS: Left in Well	CEMENT: Fill -up (Cu. Ft.)
Conductor	20"	Ν	L.S.	81.3#	40'	40'	Sand In
Fresh Water	13 3/8"	N	J-55	54.5#	600'	600'	CTS w/ Approved Class A Type Cement
Coal							
Intermediate	9 5/8"	N	J-55	36#	2000'	2000'	CTS w/ Approved Class A Type Cement
Production	5 1/2"	N	P-110	20#	17250'	17250'	2400 cu, ft. W/ 50/50 POZ Lead & Class A Tali
Tubing	2 3/8"	N	J-55	4.7#	7865'	7865'	
Liners							

Bill Halfreld 9/10/2012

TYPE	Size	Wellbore Diameter	Wall Thickness	Burst Pressure	Cement Type	Cement Yield
Conductor	20"	26"	0.438	2110	Class A Type	1.18
Fresh Water	13 3/8"	17 1/2"	0.380	2730	Class A Type	1.39
Coal						
Intermediate	9 5/8"	12 3/8"	0.352	3520	Class A Type	1.18
Production	5 1/2"	8 3/4" & 8 1/2"	0.361	12640	Class A Type	1.26
Tubing	2 3/8"	8 3/4" & 8 1/2"	0.190	7700		
Liners						

PACKERS

Kind: None Chice of Oil & Gas

Sizes: None P = 2013

Depths Set: None

21) Describe centralizer placer	ment for each casing string.	Conductor - No centra	alizers used. Fresh Water &
Coal - Bow spring centralizers	on first joint then every fourth joi	nt to 100 feet from surface	. Intermediate - Bow spring
centralizers one on the first tw	o joints and every fourth joint unti	I inside Surface casing. P	roduction - Rigid bow spring
centralizer on first joint then e	very 2 joints (free floating) throug	n the lateral and the curve	
(Note: cementing the 5 1/2" ca	asing completely in open hole late	eral and curve.)	
	ves associated with each cemen		or - 2% CaCl2.
F 1 14/-1 10 1 00/ 0 - 010	Intermediate - 2% CaCl2. Produc	tion: 2.6% Cement extend	er, 0.7% Fluid Loss Addative
0.5% High Temperature Reta	rder, 0.2% Friction Reducer.		
0.5% High Temperature Reta		ctor - The hole is drilled w	/ air and casing is ran in air
0.5% High Temperature Reta	oning procedures. <u>Condu</u>		/ air and casing is ran in air.
23) Proposed borehole condition Apart from insuring the hole is of	oning procedures. Condu	are no other conditioning pro	ocedures. Fresh Water/Coal
23) Proposed borehole condition Apart from insuring the hole is of the hole is drilled w/ air and casi	oning procedures. Conducted Conducte	are no other conditioning pro tom the casing shoe will be c	ocedures. Fresh Water/Coal
23) Proposed borehole condition Apart from insuring the hole is of the hole is drilled w/ air and casi prior to cementing. Intermediate	oning procedures. Conductean via air circulation at TD there ang is ran in air. Once casing is on bo	are no other conditioning pro tom the casing shoe will be c ng is ran in air. Once casing	ocedures. Fresh Water/Coal cleared with fresh water and ge is on bottom the casing shoe
23) Proposed borehole condition Apart from insuring the hole is of the hole is drilled w/ air and casi prior to cementing. Intermediate will be cleared with fresh water a	oning procedures. Conducted Conducte	are no other conditioning pro tom the casing shoe will be o ng is ran in air. Once casing lling soap may be utilized if the	cedures. Fresh Water/Coal cleared with fresh water and ge is on bottom the casing shoe the hole gets wet/damp during
23) Proposed borehole condition Apart from insuring the hole is of the hole is drilled w/ air and casi prior to cementing. Intermediate will be cleared with fresh water at the drilling of all air holes with the drilling are the drilling of all air holes with the drilling are	oning procedures. Conducted on the conduction of	are no other conditioning pro tom the casing shoe will be c ng is ran in air. Once casing lling soap may be utilized if the oduction - The hole is drille	cedures. Fresh Water/Coal - cleared with fresh water and gel is on bottom the casing shoe he hole gets wet/damp during d with synthetic oil base mud

*Note: Attach additional sheets as needed.

Received Office of Oil & Gas

- 5 2013

Cement Additives

- Conductor 2% CaCl2
- Freshwater/Coal 2% CaCl2
- Intermediate 2% CaCl2
- · Production
 - o 2.6% Cement extender
 - o 0.7% Fluid Loss Additive
 - o 0.5% High Temperature Retarder
 - o 0.2% Friction Reducer

Office of Oil & Gas

(PR. - 5 2013

STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS

CONSTRUCTION AND RECLAMATION PLAN AND SITE REGISTRATION APPLICATION FORM GENERAL PERMIT FOR OIL AND GAS PIT WASTE DISCHARGE

Operator Name CNX Gas Company,	LLC	OP Code 494458046	3
Watershed Buckhannon River	Qua	adrangle Century 7.5	
Elevation 1582	County_Upshur	District Warren	
Description of anticipated Pit Was	te: Fluids associated with the drilling of n	new gas wells	
Do you anticipate using more than	5,000 bbls of water to complete the	proposed well work? Yes X	No
Will a synthetic liner be used in the	e pit? Yes If so, w	hat mil.? 60 ml	
Reuse (disposal location)	
	is well? Air, freshwater, oil based, e	etc. Air and water based mud	
	Synthetic, petroleum, etc. N/A		
Additives to be used? Bactericide,			
Will closed loop system be used?	eave in pit, landfill, removed offsite,	ata Landfill	
-If left in pit and plan to s	colidify what medium will be used? permit number? MeadowFill, S&S Land	Cement, lime, N/A	
on August 1, 2005, by the Office of provisions of the permit are enforced or regulation can lead to enforcement of certify under penalty of application form and all attachment the information, I believe that the submitting false information, included Company Official Signature Company Official (Typed Name)	of law that I have personally examines thereto and that, based on my ince information is true, accurate, and adding the possibility of fine or imprisal. Jeremy Jones	Department of Environmental Pr m or condition of the general perm nined and am familiar with the quiry of those individuals immedi complete. I am aware that the comment.	otection. I understand that the nit and/or other applicable law information submitted on this ately responsible for obtaining
Company Official Title Designated	Agent - General Manager WV Gas Operation	tions	
		Office	of Oil & Gas
Subscribed and sworn before me the	nis 3rd day of Apri	, 20_13	- 2019
Kelly (i. Eddy	Notary Public	NOTARY PUBLIC OFFICIAL COM
My commission expires	eptember 18, 201	8	STATE OF WEST VIRGINIA KELLY A. EDDY RT 2 BOX 225A JANE LEW, WV 26378 MY COMMISSION FYDIRES COMMISSION FYDIR

Field Reviewed?

) Yes

Road =========	Diversion 4 / / / / /
Nogu ———————	= = Spring
Existing Fence ———————————————————————————————————	< ─ Wet Spot
Planned Fence///	/ Drain Pipe w/ size in inches
Stream	^
Open Ditch	Waterway
Rock ද්රිද්ර	Cross Drain 777777777777777777777777777777777777
	Artificial Filter Strip XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
North N	Pit: Cut Walls
Buildings	Pit: Compacted Fill Walls
Water Wells Orill Sites	Area for Land Application of Pit Waste
Proposed Revegetation Treatment: Acres Disturbed 25	Prevegetation pH 6.5
Lime according to pH test Tons/acre or to correct t	to pH 7.0
Dime Tons/acre of to correct t	W P11
Fertilizer (10-20-20 or equivalent) 500	lbs/acre (500 lbs minimum)
Mulch_Hay or Straw / 2	Cons/acre
	Seed Mixtures
Area I	Area II
Seed Type lbs/acre	Seed Type lbs/acre
Orchardgrass 25	Orchardgrass 25
Birdsfoot Trefoil 15	Birdsfoot Trefoil 15
Landino Clover 10	Landino Clover 10
Zuliulii o diatai	<u> </u>
Attach:	
Drawing(s) of road, location, pit and proposed area for land	d application. Received
	d application. Received Office of Oil & Ga
	Hecelved
Photocopied section of involved 7.5' topographic sheet.	Hecelved
Drawing(s) of road, location,pit and proposed area for land Photocopied section of involved 7.5' topographic sheet. Plan Approved by:	Office of Oil & Ga
Photocopied section of involved 7.5' topographic sheet. Plan Approved by:	Office of Oil & Ga
Photocopied section of involved 7.5' topographic sheet.	Office of Oil & Ga

west virginia department of environmental protection



Water Management Plan: Secondary Water Sources



WMP-01335

API/ID Number

047-097-03850

Operator:

Consol Energy - WV

CENT19DHS

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- •For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- •For each proposed multi-site impoundment water source identified in your water management plan (if applicable), DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.

Multi-site impoundment

Source ID: 20517 Source Name

Warder North Impoundment

Source start date:

12/1/2013

Source end date:

12/1/2014

Source Lat:

39.192505

Source Long:

-80.025198

County

Barbour

Max. Daily Purchase (gal)

Total Volume from Source (gal):

3,696,000

DEP Comments:

The intake identified above has been defined in a previous water management plan. The thresholds established in that plan govern this water management plan unless otherwise noted.

Reference: WMP-189

APPROVED JUL 2 2 2013

WMP-01335 API/ID Number 047-097-03850 Operator: Consol Energy - WV

CENT19DHS

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- •For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- •For each proposed multi-site impoundment water source identified in your water management plan (if applicable), DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.

Source ID: 20518 Source Name Warder South Impoundment Source start date: 12/1/2013

Source end date: 12/1/2014

Source Lat: 39.19097 Source Long: -80.025198 County Barbour

Max. Daily Purchase (gal) Total Volume from Source (gal): 3,570,000

DEP Comments:

The intake identified above has been defined in a previous water management plan. The thresholds established in that plan govern this water management plan unless otherwise noted.

Reference: WMP-190

Source ID: 20519 Source Name PHL28 Tank Pad Source start date: 12/1/2013

Source end date: 12/1/2014

Source Lat: 39.201747 Source Long: -80.034491 County Barbour

Max. Daily Purchase (gal)

Total Volume from Source (gal): 6,000,000

DEP Comments:

The intake identified above has been defined in a previous water management plan. The thresholds established in that plan govern this water management plan unless otherwise noted.

Reference: WMP-1332

WMP-01335 API/ID Number 047-097-03850 Operator: Consol Energy - WV

CENT19DHS

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- •For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- •For each proposed multi-site impoundment water source identified in your water management plan (if applicable), DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.

Recycled Frac Water

Source ID: 20520 Source Name PHL13 Pad Source start date: 12/1/2013

Source end date: 12/1/2014

Source Lat: Source Long: County

Max. Daily Purchase (gal)

Total Volume from Source (gal): 100,000

DEP Comments:



