

Church District, Wetzel County, W.Va.
 By Troy Oil & Gas Trust, Hundred, W.Va. (O.E./Butcher, Sec.-Treas).
 On 19 acres, surface owned by W.J. Troy, Burton, W. Va., and minerals
 by The Union Trust Co., Pittsburgh, Pa.
 Drilled under permit Wet-24, issued Feb. 24, 1930.
 Elevation, 1475' L.
 13" conductor, 13'; 10" casing, 298'; 8 $\frac{1}{4}$ ", 1666'; 6 $\frac{3}{8}$ ", 2174'.
 Coal was encountered at 877-882, 1178-1183, and 1278-1285'.
 Completion reported to Dept. of Mines March 17, 1931.
 Well was shot at 2435-2442' and 2451-2456'.
 Salt water at 2054'.
 Will make about one barrel of oil per day and has 70,000 open
 flow of gas from Injun Sand.
 Record to RCT from Mrs. Griffith Aug. 30, 1938.

	Top.	Bottom.	Thickness.
Fairview (Waynesburg) Coal, black	877	- 882	5
Bluff Sand, medium	980	- 1031	51
Slate, black, soft	1031	- 1035	4
Lime, white, hard	1035	- 1178	143
Mapletown (Sewickley) Coal, black, soft	1178	- 1183	5
Lime, white, hard	1183	- 1278	95
Pittsburgh Coal, black, soft	1278	- 1285	7
Lime, dark, hard	1285	- 1300	15
Slate, gray, soft	1300	- 1305	5
Lime, white, hard	1305	- 1325	20
Red rock, soft	1325	- 1330	5
Slate, black, soft	1330	- 1345	15
Lime, dark, medium	1345	- 1395	50
Sand, dark, medium	1395	- 1420	25
Slate and shells, black, medium	1420	- 1470	50
Red rock, soft	1470	- 1485	15
Slate shells, black, medium	1485	- 1540	55
Slate, gray, soft	1540	- 1565	25
Red rock, soft	1565	- 1590	25
Slate, black, soft	1590	- 1600	10
Lime, black, medium	1600	- 1620	20
Sand, dark, medium	1620	- 1630	10
Red rock, soft	1630	- 1667	37
Little Dunkard Sand, dark, hard	1667	- 1679	12
Red rock, soft	1679	- 1683	4
Slate shells, black, medium	1683	- 1754	71
Big Dunkard Sand, dark, medium	1754	- 1808	44 54
Slate, dark, soft	1808	- 1818	10
Sand, white, hard	1818	- 1857	39
Slate, black, soft	1857	- 1870	13
Lime, white, hard	1870	- 1910	40
Slate, black, soft	1910	- 1947	37
Gas Sand, dark, hard	1947	- 1986	39
Slate, black, soft	1986	- 2040	54
1st Salt Sand, dark, medium (little water, 2054')	2040	- 2072	32
Slate, black, soft	2072	- 2096	24
2nd Salt Sand, yellow, medium	2096	- 2148	52
Slate, gray, soft	2148	- 2176	28
3rd Salt Sand, dark, medium	2176	- 2238	62
Slate, dark, soft	2238	- 2360	122

(OVER)

W. J. TROY NO. 1 WELL (Continued).

	Top.	Bottom.	Thickness.
Red rock, soft	2360	- 2370	10
Lime, white, hard	2370	- 2380	10
Maxton Sand, dark, hard (oil, 2435-2442'; oil, 2451-2456')	2380	- 2462	82
Pencil Cave, black, soft	2462	- 2465	3
Big Lime, dark, hard	2465	- 2521	56
Big Injun Sand, dark, medium (gas at 2536-2546'; gas at 2556-2557') (black shale break, 2611-2631')	2521	- 2650	129 +
Total depth		2650	