

LATITUDE

3940

52 08

→ OGIS
7.5' 10c

LONGITUDE

7.5 OGIS topo location

7.5' 10c 0.74S
0.30W

15' 10c 0.74S
(calc.) 0.30W

Company _____

Farm _____

Elev. 1210' - 7.5' topo - Kla sl3/a1

Quad Hundred Marnington WC

County _____

District Church

WELL LOCATION MAP

File No. Wet. 128

Church District, Wetzel County, W. Va.
 By Maxton Oil & Gas Co., Scott C. Lowe, Secy., Fairmont, W. Va.
 Drilled under permit ~~Wet-128~~, issued.....1936.
 Contractor, D. W. Null and Son. *Maxton*
 Drilling commenced Sept. 16, 1936; completed, Oct. 15, 1936.
 10" casing, 181' 7"; 8 $\frac{1}{4}$ ", 1426' 7"; 6 $\frac{5}{8}$ ", 1960'.
 Record to Dept. of Mines in form of letter; not dated; filed, 12-3-36.
 Record to RCT from Mrs. Griffith Sept. 2, 1938.

	Top.	Bottom.	Thickness.
Clay, yellow, soft	0	15	15
Lime, white, hard	15	50	35
Slate, dark, soft	50	100	50
Red rock, soft	100	150	50
Lime, white, hard	150	200	50
Slate, dark, soft	200	275	75
Lime, white, hard	275	300	25
Slate, dark, soft	300	350	50
Lime, white, hard	350	375	25
Slate, dark, soft	375	475	100
Lime, white, hard	475	500	25
Slate, dark, soft	500	520	20
Shale, dark, soft	520	560	40
Slate, dark, soft	560	600	40
Lime, white, hard	600	635	35
Bluff Sand, white, hard	635	680	45
Waynesburg Coal, black, soft	680	683	3
Slate, black, soft	683	700	17
Lime, white, hard	700	765	65
Slate, dark, soft	765	785	20
Lime, white, hard	785	800	15
Slate, dark, soft	800	805	5
Lime, white, hard	805	935	130
Mapletown (Sewickley) Coal, black, soft	935	940	5
Lime, white, hard	940	955	15
Slate, dark, soft	955	965	10
Lime, white, hard	965	1026	61
Pittsburgh Coal, black, soft	1026	1034	8
Slate, dark, soft	1034	1065	31
Lime, white, hard	1065	1100	35
Red rock, soft	1100	1130	30
Sand, dark, hard <i>Murphy</i>	1130	1150	20
Red rock, soft	1150	1190	40
Lime, white, hard	1190	1195	5
Slate, dark, soft	1195	1235	40
Red rock, soft	1235	1245	10
Sand, white, hard	1245	1260	15
Slate, dark, soft	1260	1305	45
Red rock, soft	1305	1365	60
Sand, dark, hard	1365	1375	10
Slate, dark, soft	1375	1455	80
Little Dunkard Sand, white, hard	1455	1490	35
Slate, dark, soft	1490	1530	40
Big Dunkard Sand, white, hard	1530	1565	35
Slate, dark, soft	1565	1650	85
Gas Sand, dark, hard	1650	1660	10

(OVER)

J. D. (OR ESSIE) BARTBEG - NO. 3 WELL (Continued).

	Top.	Bottom.	Thickness.
Slate, dark, soft	1660	- 1720	60
1st Salt Sand, light, hard	1720	- 1760	40
Slate, dark, soft	1760	- 1850	90
2nd Salt Sand, white, hard	1850	- 1905	55
Slate, dark, soft	1905	- 1955	50
3rd Salt Sand, white, hard	1955	- 2015	60
Slate, dark, soft	2015	- 2105	90
Red rock, soft	2105	- 2143	38
Maxton Sand, light, hard (oil, 2192-96')	2143	- 2214	71
Total depth		2214	