

PITTSBURGH & WEST VA GAS

CLARKSBURG WEST VA

Well No. 1500

W. J. Birmingham

COMPLETION DATA SHEET
NO. 2
FORMATION RECORD

Name	Color	Texture	Initial Depth	Top	Bottom	Thickness	Total Depth	Remarks
Clay				0	2	19	19	
Red Rock				19	4	30	49	
Slate				49	18	110	159	
Red Rock				159	18	23	182	
Lime Shells				182	20	18	200	
Red Rock				200	21	10	210	
Sand				210	22	10	220	
Slate&Shells				220	23	60	280	
Lime				280	30	65	345	
Slate&Shells				345	30	135	480	
Sand				480	48	40	520	
Slate&Lime				520	57	50	570	
Sand				570	61	45	615	
Lime				615	78	166	781	
M.T. Coal				781	78	6	787	
Lime				787	84	77	864	
Slate				864	88	20	884	
Fgh. Coal				884	88	6	890	
Lime				890	88	10	900	
Slate & Shells		Hard		900	90	60	960	
Red Rock				960	96	6	966	
Slate & Lime		Soft		966	102	60	1026	
Red Rock				1026	119	170	1196	
Lime		Soft		1196	122	23	1219	
Sand	White	Hard		1219	122	13	1232	
Slate&Red Rock	"	"		1232	122	149	1381	
Sand				1381	122	40	1421	
Coal	White			1421	142	2	1423	
Lime				1423	144	22	1445	
Sand				1447	147	22	1475	
Slate				1475	147	22	1497	
Lime	Dark			1497	152	23	1520	
Sand		Hard		1520	152	63	1583	
Coal	White	"		1583	152	3	1606	
Lime				1606	152	20	1626	
Slate				1626	152	34	1660	
Sand				1660	152	25	1685	
Coal	White	Hard		1685	152	2	1690	
Lime				1690	152	12	1702	
Slate	White	Hard		1702	170	8	1710	
Sand	Black	Soft		1710	172	45	1755	
Slate&Shells	White			1755	172	42	1800	
Salt Sand				1800	182	134	1934	
Slate	White	Hard	0-1820'	1934	182	36	1970	
	Black	Soft			182			

Continued to Sheet No. 2

PITTSBURGH & WEST VA GAS COMPANY.

PITTSBURGH & WEST VA. COAL

CLARK HILL, WEST VA.

1906

CLARK HILL

Name	Color	Character	Interval in Feet	Top	Bottom	Thickness	Total Depth	Remarks
Red Rock Shells		Hard		1970	2010	40	2010	
Sand		"	0-2013'	2010	2023	13	2023	
Slate	Dark	Soft		2023	2027	4	2027	
Lime	White	Hard		2027	2168	141	2168	
Big Injun		"	0-2175'	2168	2225	57	2225	
Slate Shells	White	"		2225	2440	215	2440	
Lime	"	"		2440	2548	108	2548	
Slate Shells	"	"		2548	2670	122	2670	
Sand Shells	Slate	Hard		2670	2725	55	2725	
Red Rock		"		2725	2803	78	2803	
Sand	White	"		2803	2827	24	2827	
Slate	Dark	Soft		2827	2841	14	2841	
Sand	White	Hard		2841	2880	39	2880	
Slate	Dark	Soft		2880	2924	44	2924	
20 Ft. Sand	White	Hard		2924	2928	4	2928	
Slate	Dark	"		2928	2965	37	2965	
Garden Stray	Pink	"		2965	2965	0	2965	
Slate	White	"		2965	3045	80	3045	
Garden Sand	"	Hard		3045	3073	28	3073	
Slate Shells	"	Soft		3073	3105	32	3105	
4th. Sand	"	Hard	0-3084'	3073	3105	32	3105	
Slate Shells	"	"		3105	3493	388	3493	
						Total Depth	3493'	

shot
Well was not shot at shot 20 qts. 4th. SAND

Salt
Fresh water

Well was
2-2/3
2000

No. 1000

PITTSBURGH & WEST VIRGINIA GAS CO.

Maplestown, Penna.
No. 1000
200 East Main Street,
MAYNESBURG, PENNA.

CLARKSBURG, WEST VA.

June 25th, 1935

WELL AND LOCATION

Church Dist.

Wetzel Court

Lee & Nettie Church
Property - Owner

Well No. 1804

Barton, West Va.

Wm. L. Cunningham Pa.

OPERATOR OF THIS WELL IS PITTSBURGH & WEST VIRGINIA GAS CO. THE DEPARTMENT ONE COPY TO BE RETURNED TO THE OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESS.

AFFIDAVIT

STATE OF WEST VIRGINIA

COUNTY OF Wetzel

Martin Horner and Earl H. Wright.

being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Pittsburgh & West Va. Gas Co., well operator and participated in the work of plugging and filling the above well, that said work was commenced on the

15th day of June 1935, and that the well was plugged and filled in the following manner:

Manner in which sand was plugged: Total depth of well 3483 feet.
Previously filled to 3092 feet.
Clay 3092 to 3073 feet, Cement 3073 to 3065 feet, Clay 3065 to 2783 feet, Cement 2783 to 2773 feet.
Hole bridged at 2415 feet, (30 feet below B.I. Sand.) Clay 2415 to 2134 feet
Lead plug 2134 to 2123 feet, (In Big Lime.) Cement 2123 to 2123 feet.
Hole bridged at 1964 feet, (30 feet below Salt Sand.) Clay 1964 to 1365 feet
(20 feet above sand.) Cement 1365 to 1355 feet.

Manner in which coal was plugged:
Run 27 vent pipe on suitable packer at 920 feet, (30 feet below Pgh. Coal.)
Cement from 920 to 864 feet, (20 feet above Pgh. Coal.) Clay from 864 to 817 feet, (30 feet below Mapletown Coal.) Cement from 817 to 761 feet, (20 feet above Mapletown Coal.) Clay from 761 feet to surface.

Witness my hand and seal of office at Clarksburg, West Virginia, this 25th day of June, 1935.
Wm. L. Cunningham
Cement & Lox Pipe Foot, Pittsburgh & West Virginia Gas Company #1804.

Subscribed and sworn to before me this 25th day of June, 1935.