

Church District, Wetzel County, W. Va.

By The Pure Oil Co.

Survey No. 38. Elevation, 1390' B.

Commenced Oct. 26, 1903; completed Dec. 3, 1903.

Small show of oil in first pay. Filled up 800 ft. first

24 hrs. with oil from second pay. Gas very light.

Liner put in single section, set on bottom of hole, and

36 1/2 ft. of bottom perforated.

From bottom of casing to top of Maxton Sand, 122 feet.

April 4, 126 ft. liner put in on top of sand. Packer

set at bottom of six-inch casing.

1 1/2" conductor; 10" casing, none in; 8 1/2", 1590'; 6-5/8", 2196';

5-3/16" liner, 1444'.

Shot Dec. 10, 1903, by C. C. Fisher, with 70 qts. in 1st and

second pays; 2nd pay, 2 shells, 50 qts.; 10' shell;

depth of well when shot, 2370'; depth top of shot, 2360';

1st pay, 1 shell, 20 qts.; 5' shell; 7' anchor; depth of

well when shot, 2360'; depth top of shot, 2348'; bridged.

Shot March 6, 1906, by Fisher Torpedo Co., with 90 qts.;

21' shell; 17' anchor; shells passed; depth of well when

shot, 2370'; depth top of shot, 2318'; bridged.

Record from E. Townley, Room 2308, 35 E. Wacker Drive,

Chicago, Ill., March 13, 1931.

	Top.	Bottom.
Pittsburgh Coal	1190	
Little Dunkard Sand	1575	1600 - 1625
Big Dunkard Sand		1655 - 1690
Salt Sand		2120 - 2190
Red cave		2256.
Maxton Sand (1st pay, 2350-2352'; 2nd pay, 2365-2370')		2318
Total depth		2373