



M.C. - MARCH 1943

Latitude 39° 05'

Longitude 81° 30'

New Location
 Drill Deeper
 Abandonment

See Vol. XVI. p. 710.

PRO. LOC. 1.5 MILES N.W. OF WINDY

*3.08-S
S.H.S
Z.B.W
7-C (G-5)*

Company	COLUMBIAN CARBON CO.
Address	BOX 873 CHARLESTON W. VA.
Farm	VIRGIE MASON
Tract	Acres 130.0 Lease No. T-2067
Well (Farm) No.	ONE Serial No. GW-713
Elevation (Spirit Level)	897.8
Quadrangle	BELLEVILLE (S.E.) -7-
County	WIRT District TUCKER
Engineer	<i>J. Sell</i>
Engineer's Registration No.	772
File No.	Drawing No. 211
Date	APRIL 12, 1943 Scale 1" = 1320'

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. WIRT-177

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
W E L L R E C O R D

Permit No. Wirt 177		Dry Hole
Belleville S.E. Quad.		CASING & TUBING
Company	Columbian Carbon Company	
Address	Box 873, Charleston, W.Va.	16 19'7
Farm	Virgie Mason Acres 130	13 3/8 957'6 0
Location	Tucker Creek	10 1/2 1375' 0
Well No	1 (GW 713) Elev. 899.9 DF	8 5/8 2379'4 0
District	Tucker Wirt County	7 5168'4
Surface	Mrs. Hannah Daugherty	
	1719 20th St., Parkersburg, W.Va.	
Mineral		
Commenced	4-26-43	
Completed	8-12-43	
Date shot	8-13-43 Depth 5248 to 5288	
	with 266-2/3# Atlas Gelatin	
Fresh Water	784'2-14" blrs. / hr.;	
Salt Water	1335 1/2 blr. / hr.; 1420 2-9 1/2" Blrs/hr.	
	1600 4-9 1/2" Blrs. / hr.; 1874 H.F.	

STATUS OF WELL BEFORE PLUGGED

Red Clay	0	10	Maxon Sand	1982	2121
Lime	10	22	Slate	2121	2124
Red Rock	22	38	Lime - <i>Big lime plus</i>	2124	2443 ?
Sand	38	50	Slate	2443	2470
Red Rock	50	120	Shale - <i>same as?</i>	2470	2485
Lime	120	132	Lime - <i>Rosa Bologna?</i>	2485	2520
Red Rock	132	170	Slate & Shells	2520	3816
Sand	170	185	Lime	3816	3953
Red Rock	185	192	Slate & Shells	3953	4030
Sand	192	253	Shale	4030	4092
Red Rock	253	273	Slate & Shells	4092	4179
Slate & Red Rock	273	303	Shale	4179	4215
Slate	303	310	Slate & Shells	4215	4773
Red Rock	310	327	Shale	4773	5117 SLM
Slate	327	337	✓ Corniferous Lime SLM	5117	5248 SLM
Red Rock	337	390	✓ Oriskany Sand	5248 SLM	5294
Lime	390	430	✓ Lime - <i>Heidenberg</i>	5294	5328 SLM
Red Rock	430	458	TOTAL DEPTH		5328 SLM
Slate	458	470			
Sand	470	483	Show gas 5273		(485)
Red Rock	483	530			
Lime	530	550	CEMENT RECORD:		
Sand	550	631	5-7-43 Aquagelled 13 3/8" casing. Ran		
Red Rock	631	666	25 sacks aquagel and 1 bale Fibrotex.		
Sand	666	712	Returns 890'.		
Red Rock	712	725			
Lime	725	756	5-30-43 Aquagelled 10 1/2" casing. Ran 25		
Sand	756	838	sacks aquagel and 1 bale Fibrotex.		
Slate	838	895	Returns while floating pipe in.		
Sand	895	914			
Slate	914	935	6-22-43 Aquagelled 8 5/8" casing. Ran		
Red Rock	935	969	26 sacks aquagel and 1 bale Fibrotex.		
Lime	969	972	Returns 1869'.		
Red Rock	972	1070			
Slate	1070	1135	7-27-43 Aquagelled 7" casing. Ran 50		
Red Rock	1135	1197	sacks aquagel and 4 bales Fibrotex.		
Sand	1197	1215	Returns while running pipe.		
Slate & Shells	1215	1224			
Lime	1224	1254			
Slate	1254	1275			
Sand	1275	1364			
Slate	1364	1374			
Lime	1374	1485			
Sand	1435	1445			
Slate	1445	1456			
Sand	1456	1544			
Lime	1544	1562			
Slate & Shells	1562	1640			
Sand	1640	1693			
Slate	1693	1836			
✓ Salt Sand	1836	1980			
Slate	1980	1982			

5117 5248 5294