

2.38-S  
~~2.41-S~~  
1.59-W  
1.56-W  
3 C (G-5)  
+

B. & O. R.R.



Robt Abbott

N 7 1/4° E 100.6 feet

Millard Abbott  
7 1/2 A

S 16° 30' E 340'

50'

S 10° W 101.5 feet

Stake N 77° 44' E 204' 1/2  
N 77° 44' E 204' 1/2  
509'

N 10° 50' E 371'

N 10° 50' E 371'

S 73° 04' W 151 1/2'

M. Abbott

To New England 1/4 mi.

New Location:   
Drill Deeper:   
Abandonment:

Company B. H. Purnam, Operator.  
Address 1<sup>st</sup> Nat. Bank, Marietta Ohio.  
Farm Millard Abbott  
Tract 1 Acres 7 1/2 Lease No. \_\_\_\_\_  
Well (Farm) No. 1 Serial No. \_\_\_\_\_  
Elevation (Spirit Level) 302'  
Quadrangle Bellefleur **NW.**  
County Wood District Harris  
Engineer Robert R. Anderson  
Engineer's Registration No. 296  
File No. \_\_\_\_\_ Drawing No. \_\_\_\_\_  
Date Nov 13 52 Scale 1 in = 200 feet

STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION  
CHARLESTON

WELL LOCATION MAP  
FILE NO. W00-380

+ Denotes location of well on United States Topographic Maps, scale 1 to 62 500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing

DeepWell



STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

CORRECTED WELL RECORD

*Bellville*

WELL RECORD

Permit No. Woo-387 380

Oil or Gas Well Gas  
(KIND)


Company B. H. Putnam, Operator  
Address 512 Third Street, Marietta, Ohio  
Farm Millard Abbott Acres 192  
Location (waters) \_\_\_\_\_  
Well No. 1 Elev. 837  
District Harris County Wood  
The surface of tract is owned in fee by M. Abbott  
Address \_\_\_\_\_  
Mineral rights are owned by \_\_\_\_\_  
Address \_\_\_\_\_  
Drilling commenced December 2, 1952  
Drilling completed January 24, 1953  
Date Shot Hydrafrac From \_\_\_\_\_ To \_\_\_\_\_  
With \_\_\_\_\_  
Open Flow /10ths Water in \_\_\_\_\_ Inch  
/10ths Merc. in \_\_\_\_\_ Inch  
Volume 1,560,000 Cu. Ft.  
Rock Pressure 1510 lbs. \_\_\_\_\_ hrs.  
Oil None bbls., 1st 24 hrs.  
Fresh water None feet \_\_\_\_\_ feet  
Salt water None feet \_\_\_\_\_ feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			
16			Kind of Packer
13			Baker Model 'K'
10	101'	101'	Size of 5"
8 1/4	981'		
7	1773	1773'	Depth set 4310
5 3/16	4320'	4320'	
8			Perf. top
2			Perf. bottom
Liners Used			Perf. top
			Perf. bottom

CASING CEMENTED 5" SIZE 4320 No. Ft. 1/18/53 Date

COAL WAS ENCOUNTERED AT \_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
\_\_\_\_\_ FEET \_\_\_\_\_ INCHES \_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
\_\_\_\_\_ FEET \_\_\_\_\_ INCHES \_\_\_\_\_ FEET \_\_\_\_\_ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Surface			0	10			
Sand			10	20			
Rock	Red		20	40			
Sand			40	70			
Rock	Red		70	165			
Slate			165	200	4231	4325	
Sand			200	280	837	837	
Slate			280	360			
Rock	Red		360	395	3394	3488	
Slate	Gray		395	495			
Rock	Red		495	505			
Slate			505	640			
Rock	Red		640	731			
Sand			731	750			
Slate	Dark		750	845			
Lime Shells			845	880			
Slate			880	920			
Rock	Pink		920	940			
Shells			940	970			
Rock	Red		970	1270			
Sand			1270	1315			
Slate			1315	1350			
Sand			1350	1407			
Slate			1407	1535			
Sand			1535	1552			
Injun			1552	1753			
Slate			1753	2027			
Shell			2027	2032			
Slate - <i>Coffee Shale</i>			2032	2051			
Berea			2051	2054			
Slate			2054	3200			
Cinnamon			3200	3690			
Slate			3690	4231			
Lime - <i>Onondaga</i>			4231	4325			
Oriskany			4325	4351			



(Over)

475