

CORE ANALYSIS RESULTS

#733

CP-1-4875

Company	THE PRESTON OIL COMPANY	Formation	AS NOTED	File	CP-10-1015
Well	V-2020	Core Type	DIAMOND	Date Report	9-11-63
Field	GRANNYS CREEK	Drilling Fluid	AS NOTED	Analysts	WELBORNE-
County	CLAY	State	W. VIRG.	Elev.	1208'
		Location			BOYLE

Lithological Abbreviations

SAND-SO SHALE-SH LIME-LM	DOLOMITE-DOL CHERT-CH GYPSUM-GYP	ANHYDRITE-ANHY CONGLOMERATE-CONG FOSSILIFEROUS-FOSS	SANDY-SBY SHALY-SHY LIMY-LMY	FINE-FN MEDIUM-MED COARSE-CSE	CRYSTALLINE-XLN GRAIN-GRN GRANULAR-GRNL	BROWN-BRN GRAY-GY VUGGY-VGY	FRACTURED-FRAC LAMINATION-LAM STYLOLITIC-STY	SLIGHTLY-SL/ VERY-V/ WITH-W/
--------------------------------	--	---	------------------------------------	-------------------------------------	---	-----------------------------------	--	------------------------------------

SAMPLE NUMBER	DEPTH FEET	PERMEABILITY MILLIDARCYS		POROSITY PER CENT	RESIDUAL SATURATION PER CENT PORE		SAMPLE DESCRIPTION AND REMARKS
		PERM. MAX.	PERM. 90°		OIL	TOTAL WATER	

BIG LIME FORMATION - WHOLE CORE ANALYSIS - OIL EMULSION MUD DRILLING FLUID

1	2031.0-32.7	<0.1	<0.1	0.9	0.0	58.6	Lm
2	32.7-34.4	<0.1	<0.1	0.8	0.0	26.8	Lm
3	34.4-36.0	<0.1	<0.1	1.0	0.0	79.2	Lm
4	36.0-37.8	<0.1	<0.1	1.7	0.0	59.0	Lm, shy
5	37.8-39.5	<0.1	<0.1	1.0	0.0	77.0	Lm
6	39.5-41.2	<0.1	<0.1	0.9	0.0	50.0	Lm, sl/shy
7	41.2-42.3	<0.1	<0.1	1.3	0.0	33.0	Lm, sl/shy
8	42.3-43.4	<0.1	<0.1	1.1	0.0	59.8	Lm
9	43.4-44.9	<0.1	<0.1	2.6	5.0	89.2	Lm, sl/chalky
10	2044.9-46.0	<0.1	<0.1	11.2	37.9	52.3	Lm, chalky

BIG INJUN SAND FORMATION - CONVENTIONAL ANALYSIS - CRUDE OIL DRILLING FLUID

11	2046.0-47.0	0.1		10.5	46.7	25.7	Sd, fn grn
12	47.0-48.0	28		18.4	69.5	15.2	Sd, fn grn
13	48.0-49.0	0.4		14.4	61.1	16.0	Sd, fn grn
14	49.0-50.0	0.1		15.0	64.7	17.3	Sd, fn grn
15	50.0-51.0	0.4		17.2	57.5	18.0	Sd, fn grn
16	51.0-52.0	2.2		10.9	45.0	35.8	Sd, fn grn
17	52.0-53.0	0.1		10.5	28.6	32.4	Sd, fn grn
18	53.0-54.0	3.8		12.5	39.2	33.6	Sd, fn grn
19	54.0-55.0	22		15.3	62.8	12.4	Sd, fn grn
20	55.0-56.0	0.1		7.5	26.7	20.0	Sd, med-cse grn
21	56.0-57.0	1.1		12.0	56.7	12.5	Sd, fn grn
22	57.0-58.0	1.3		15.2	50.6	21.7	Sd, fn grn
23	58.0-59.0	2.9		12.1	32.2	33.9	Sd, fn grn
24	59.0-60.0	17		10.9	45.0	13.8	Sd, cse grn
25	60.0-61.0	0.1		7.9	25.3	25.3	Sd, med-cse grn
26	61.0-62.0	11		21.9	58.8	19.2	Sd, fn grn
27	62.0-63.0	0.1		20.9	52.5	21.0	Sd, fn grn
28	63.0-64.0	8.8		19.7	56.3	22.6	Sd, fn grn
29	64.0-65.0	53		8.1	58.0	12.3	Sd, cse grn
30	65.0-66.0	282		8.3	48.2	8.4	Sd, cse grn
31	66.0-67.0	0.1		8.8	21.6	21.6	Sd, fn grn

1305

145

These analyses, opinions or interpretations are based on observations and materials supplied by the client to whom, and for whose exclusive and confidential use, this report is made. The interpretations or opinions expressed represent the best judgment of Core Laboratories, Inc. (all errors and omissions excepted); but Core Laboratories, Inc. and its officers and employees, assume no responsibility and make no warranty or representations, as to the productivity, proper operations, or profitability of any oil, gas or other mineral well or sand in connection with which such report is used or relied upon.

CORE LABORATORIES, INC.
 Petroleum Reservoir Engineering
 DALLAS, TEXAS

File CP-1-4875, CP-10-1015 Page No. 2
 Well V-2020

CORE ANALYSIS RESULTS

SAMPLE NUMBER	DEPTH FEET	PERMEABILITY MILLIDARCYs	POROSITY PER CENT	RESIDUAL SATURATION PER CENT PORE		SAMPLE DESCRIPTION AND REMARKS
				OIL	TOTAL WATER	
32	2067.0-68.0	490	10.7	55.2	4.7	Sd, cse grn
33	68.0-69.0	192	18.4	65.7	8.7	Sd, cse grn
34	69.0-70.0	0.1	16.1	33.5	34.8	Sd, fn grn
35	70.0-71.0	0.1	20.4	28.0	28.0	Sd, fn grn
36	71.0-72.0	2.9	19.4	35.6	33.0	Sd, fn grn, sl/shy
37	72.0-73.0	3.0	22.1	29.4	27.6	Sd, fn grn
38	73.0-74.0	4.4	21.0	33.8	31.9	Sd, fn grn
39	74.0-75.0	3.7	21.8	34.8	26.6	Sd, fn grn
40	75.0-76.0	<0.1	18.7	39.0	25.6	Sd, fn grn
41	76.0-77.0	5.2	18.9	38.0	33.3	Sd, fn grn
42	77.0-78.0	17	19.7	28.5	31.4	Sd, fn grn
43	78.0-79.0	2.6	19.5	36.4	36.4	Sd, fn grn
44	79.0-80.0	54	21.3	43.6	28.4	Sd, fn grn
45	80.0-81.0	0.4	19.2	26.0	31.8	Sd, fn grn, sl/shy
46	81.0-82.0	3.0	19.4	38.1	37.2	Sd, fn grn
47	82.0-83.0	3.6	20.5	24.4	33.2	Sd, fn grn
48	83.0-84.0	6.3	22.9	30.5	35.8	Sd, fn grn
49	84.0-85.0	3.3	22.0	52.8	28.2	Sd, fn grn
50	85.0-86.0	4.9	22.3	53.0	30.5	Sd, fn grn
51	86.0-87.0	1.2	21.5	53.5	39.7	Sd, fn grn
52	87.0-88.0	2.7	19.2	46.8	33.3	Sd, fn grn
53	88.0-89.0	0.1	13.9	20.8	26.6	Sd, fn grn
54	89.0-90.0	<0.1	17.8	18.5	46.6	Sd, v/fn grn
55	90.0-91.0	<0.1	17.9	10.6	58.1	Sd, v/fn grn
56	91.0-92.0	<0.1	15.3	11.1	79.0	Sd, v/fn grn
57	2092.0-92.6	<0.1	14.3	7.7	81.2	Sd, v/fn grn
	2092.6-93.5					Sh
58	2093.5-94.0	<0.1	15.9	13.8	56.0	Sd, v/fn grn
59	94.0-95.0	<0.1	19.1	11.5	52.8	Sd, v/fn grn
60	95.0-96.0	<0.1	9.7	11.3	44.3	Sd, siltstone
61	96.0-97.0	<0.1	17.1	9.4	53.4	Sd, v/fn grn
62	97.0-98.0	<0.1	4.9	4.1	77.6	Sd, v/fn grn
63	2098.0-99.5	<0.1	4.3	0.0	86.1	Sd, v/fn grn
	2099.5-00.5					Sh
64	2100.5-01.0	<0.1	4.8	0.0	85.3	Siltstone
65	2101.0-02.8	<0.1	11.4	0.0	89.4	Siltstone
	2102.8-04.0					Sh
66	2104.0-05.0	<0.1	8.7	0.0	87.2	Siltstone
	2105.0-05.4					Sh, red
67	2105.4-06.0	<0.1	5.5	0.0	83.7	Siltstone

These analyses, opinions or interpretations are based on observations and materials supplied by the client to whom, and for whose exclusive and confidential use, this report is made. The interpretations or opinions expressed represent the best judgment of Core Laboratories, Inc. (all errors and omissions excepted); but Core Laboratories, Inc. and its officers and employees, assume no responsibility and make no warranty or representations, as to the productivity, proper operations, or profitability of any oil, gas or other mineral well or sand in connection with which such report is used or relied upon.

CORE ANALYSIS RESULTS

SAMPLE NUMBER	DEPTH FEET	PERMEABILITY MILLIDARCY	POROSITY PER CENT	RESIDUAL SATURATION PER CENT PORE		SAMPLE DESCRIPTION AND REMARKS
				OIL	TOTAL WATER	
68	2106.0-07.0	<0.1	4.3	0.0	83.6	Siltstone
69	2107.0-08.0	<0.1	8.9	0.0	96.5	Siltstone

THIS IS THE FINAL REPORT.

DISTRIBUTION: 7 CC: THE PRESTON OIL COMPANY
ATT: WILLIAM D. CONNER
BOX 2319
COLUMBUS 16, OHIO