

C. E. Albertson, Trustee No. 6(530) Well

Pocatalico District, Putnam County, W. Va.

By West Virginia Gas Corporation, Charleston, W. Va.

Located 1.79 Mi. S. of 38 30' and 1.57 Mi. W. of 81 45' - NE -

Saint Albans Quadrangle.

Elevation 976.37' L. (ground)

Permit Put - 313

Drilling commenced Aug. 8, 1945; completed Sept. 12, 1945.

7" casing, 1860' 4".

Acidized Sept. 10, 1945, with 1000 gallons.

Gas well; volume 440 M.

Rock pressure 296 lbs. in 24 hrs.

Section based on samples from 1844 to 1945', examined by J. H. C. Martens.

Top Bottom Thickness

Greenbrier Limestone, 101+ feet.

1844			Top Big Lime in record
1844	1874	30	Limestone, very light brown to white
1874	1889	15	Limestone, very light-brown to white, oolitic; many fragments are very porous (gas, 1883-1887')
1889	1894	5	Limestone, very light brown, compact
1894	1915	21	Limestone, light-brown, with many small oolites and a little sand
1915	1920	5	Limestone, light-brown, oolitic and sandy; much more sand than interval above
1920	1924	4	Limestone, nearly white, oolitic, very porous; pores between oolites are lined with very small calcite crystals (gas, 1920-1924')
1924	1931	7	Limestone, nearly white, oolitic, not visibly porous
1931	1945	14	Limestone, nearly white, dolomitic
	1945		Total depth; plugged back to 1939'