

SOLMON DAY NO. 1 WELL.

70071

Union District, Harrison County, W. Va.

By.....

LOCATION Not Found

J. E. Trainer, Contractor.

Elevation.....

Drilling commenced Aug. 15, 1913; completed Oct. 10, 1913.

10" casing, 590'; 8 1/2" 1148'; 6" 2070'; all left in.

Minute pressure: 1/2 min., 70 lbs.; 1 min., 210 lbs.; 2 min., 245 lbs.;

3 min., 254 lbs.; 4 min., 258 lbs.; 5 min., 260 lbs.; 6 min.,

262 lbs.; 7 min., 263 lbs.; 8 min., 264 lbs.; 9 min., 265 lbs.;

10 min., 266 lbs. Rock pressure, 325 lbs.

Well showed 70/10 Mercury through 2" opening.

Top of perforated joint, 2778'; top of packer, 2733'; bottom of packer, 2737'.

7-16-18. Cleaned out and retubed 2" tubing. Top of packer, 2736';

bottom of packer, 2740'. 42/10 Water through 2". 80# Rock

pressure, 15 min.

Abandoned July 18, 1925.

Record in Eastern Petroleum Co. Well Record book of Clifton Oil & Gas Co.

	Top.	Bottom.
(water at 95')		(water at 125')
Native coal	390	393
Pittsburgh Coal	700	705
Little Dunkard Sand	1050	1085
Big Dunkard Sand	1120	1170
Gas Sand	1245	1280
First Salt Sand	1400	1455
Second Salt Sand	1565	1700
3rd Salt Sand	1735	1795
Maxton Sand	1875	1890
Little Lime	2027	2037
Pencil Cave	2037	2043
Big Lime	2043	2115
Big Injun Sand	2115	2195
Squaw Sand	2250	2265
Gantz Sand	2254	2484?
Berea Sand	2288	2358?
Fifty-foot Sand	2580	2600
Thirty-foot Sand	2665	2690
Gordon Strey Sand	2717	2747
Gordon Sand (gas, 2769')	2767	2793
Total depth		2799
Total depth (second) (after deepening)		3021

Date of deepening or record of deepening not given.