



Company EVERITT-WHITING INC.  
KANAWHA ACCOUNT

Address OKEMAH, OKLA

Farm J.V.R. SKINNER

Tract \_\_\_\_\_ Acres 246 Lease No. \_\_\_\_\_

Well (Farm) No. 5 13-17 Serial No. \_\_\_\_\_

Elevation (Spirit Level) # 13-1135.20 & 17-990.00

Quadrangle CLENDENIN

County KANAWHA District ELK

Engineer R.F. Kye

Engineer's Registration No. 804

File No. \_\_\_\_\_ Drawing No. \_\_\_\_\_

Date 2-21-49 Scale 1" = 500'

STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION  
CHARLESTON

WELL LOCATION MAP  
FILE NO. KAN-611-A-#13  
KAN-612-A-#17

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.



J. V. R. SKINNER NO. 13 WELL.

611A

Elk District, Kanawha County, W. Va.  
 By Everitt-Whiting, Inc., Okemah, Okla.  
 Abandoned under permit Kan-.....-A?  
 On 246 acres, on Right Fork of Blue Creek.  
 Elevation, 1135.20' L.

Drilling completed Jan. 6, 1916.

7" O. D. casing, 1785'; 5 $\frac{1}{2}$ "", 1910'; 2" tubing, 2173'; all left in.

Oil well. Record to Dept. of Mines stamped March 5, 1949.

Record to RCT from Mrs. Griffith April 18, 1949. Old File No. 1379.  
 Shot May 5, 1915, at 2163-2173', with 20 qts.; March 9, 1916, at 2163-2173',  
 with 20 qts.; and May 2, 1917, at 2163-2173', with 30 qts.

	Top.	Bottom.
Coal	390	393
Coal	500	504
Salt Sand	1074	1565
Maxton Sand	1672	1690
Big Lime	1770	1925
Squaw Sand	1980	2008
Weir Sand (gas, 2055') (oil, 2129')	2050	2173
Total depth		2173





Completed no inspection  
1379

STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

WELL RECORD

Permit No. 611-A

Oil or Gas Well X (KIND)

Company Everitt - Whiting, Inc.,  
 Address Okemah, Okla.  
 Farm J. V. R. Skinner Acres 248  
 Location (waters) Right Fork, Blue Creek  
 Well No. 13 Elev. 1155.20'  
 District FLK County Kanawha  
 The surface of tract is owned in fee by \_\_\_\_\_  
 Address \_\_\_\_\_  
 Mineral rights are owned by \_\_\_\_\_  
 Address \_\_\_\_\_  
 Drilling commenced \_\_\_\_\_  
 Drilling completed January 6, 1916  
 Date Shot From \_\_\_\_\_ To \_\_\_\_\_  
 With \_\_\_\_\_  
 Open Flow /10ths Water in \_\_\_\_\_ Inch  
 /10ths Merc. in \_\_\_\_\_ Inch  
 Volume \_\_\_\_\_ Cu. Ft.  
 Rock Pressure \_\_\_\_\_ lbs. \_\_\_\_\_ hrs.  
 Oil \_\_\_\_\_ bbls., 1st 24 hrs.  
 Fresh water \_\_\_\_\_ feet \_\_\_\_\_ feet  
 Salt water \_\_\_\_\_ feet \_\_\_\_\_ feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16			
13			
10			Size of
8 1/4			
6 5/8			Depth set
5 3/16	27" OD. 1785	1785'	
3	5-1/2 1910	1910	Perf. top
2			Perf. bottom
Liners Used	2173'	2173'	Perf. top
			Perf. bottom

CASING CEMENTED \_\_\_\_\_ SIZE \_\_\_\_\_ No. Ft. \_\_\_\_\_ Date \_\_\_\_\_  
 COAL WAS ENCOUNTERED AT \_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
 \_\_\_\_\_ FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES  
 \_\_\_\_\_ FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Coal			390	393			
Coal			500	504			
Salt Sand			1074	1565			
Maxon Sand			1672	1690			
Big Lime			1770	1925			
Squaw Sand			1980	2008			
Weir Sand			2050	2173			
Gas			2055				
Oil			2129				
Total Depth				2173'			
SHOT RECORD			TOP	BOTTOM			
			2163	2173	- 20	ts.	
			2163	2173	- 20	"	
			2163	2173	- 30	"	

