

WR-35
Rev (9-11)

State of West Virginia
Department of Environmental Protection
Office of Oil and Gas
Well Operator's Report of Well Work

DATE: January 30, 2014
API#: 547-103-02772

Farm name: Denoon Trust, Janie Operator Well No.: 01-Bowyers #6H

LOCATION: Elevation: 1,156' Quadrangle: New Martinsville

District: Magnolia County: Wetzel
Latitude: 13,440 Feet South of 39 Deg. 42 Min. 30 Sec.
Longitude 3,030 Feet West of 80 Deg. 50 Min. 00 Sec.

Company: **Stone Energy Corporation**

Address:	Casing & Tubing	Used in drilling	Left in well	Cement fill up Cu. Ft.
6000 Hampton Center, Suite B Morgantown, WV 26505	20"	80'	80'	GTS
Agent: Tim McGregor	13.375"	1,117'	1,117'	1,054 - CTS
Inspector: Derek Haught	9.625"	2,247'	2,247'	711 Lead - 200 Tab - CTS
Date Permit Issued: 6/21/2012	5.5"		12,709'	945 Lead - 2,290 Tab
Date Well Work Commenced: 11/4/2012	2.375"		6,685'	
Date Well Work Completed: 9/1/2013				
Verbal Plugging:				
Date Permission granted on:				
Rotary <input checked="" type="checkbox"/> Cable <input type="checkbox"/> Rig <input type="checkbox"/>				
Total Vertical Depth (ft): 6,444				
Total Measured Depth (ft): 12,722				
Fresh Water Depth (ft.): 90				
Salt Water Depth (ft.): None Reported				
Is coal being mined in area (N/Y)? No				
Coal Depths (ft.): 831				
Void(s) encountered (N/Y) Depth(s) N/A				

OPEN FLOW DATA (If more than two producing formations please include additional data on separate sheet)

Producing formation Marcellus Pay zone depth (ft) 6,756' to 12,605'
Gas: Initial open flow 170 MCF/d Oil: Initial open flow 0 Bbl/d
Final open flow 1,750 MCF/d Final open flow 0 Bbl/d
Time of open flow between initial and final tests 261 Hours
Static rock Pressure 2700 psig (surface pressure) after 154 Hours

Second producing formation _____ Pay zone depth (ft) _____
Gas: Initial open flow _____ MCF/d Oil: Initial open flow _____ Bbl/d
Final open flow _____ MCF/d Final open flow _____ Bbl/d
Time of open flow between initial and final tests _____ Hours
Static rock Pressure _____ psig (surface pressure) after _____ Hours

I certify under penalty of law that I have personally examined and am familiar with the information submitted on this document and all the attachments and that, based on my inquiry of those individuals immediately responsible for obtaining the information I believe that the information is true, accurate, and complete.

W. J. [Signature]
Signature

1/30/2014
Date

103.02772

Were core samples taken? Yes _____ No X

Were cuttings caught during drilling? Yes X No _____

Were Electrical, Mechanical or Geophysical logs recorded on this well? If yes, please list MWD Gamma Ray, Mud Log, and CBL

NOTE: IN THE AREA BELOW PUT THE FOLLOWING: 1). DETAILS OF PERFORATED INTERVALS, FRACTURING OR STIMULATING, PHYSICAL CHANGE, ETC. 2). THE WELL LOG WHICH IS A SYSTEMATIC DETAILED GEOLOGICAL RECORD OF THE TOPS AND BOTTOMS OF ALL FORMATIONS, INCLUDING COAL ENCOUNTERED BY THE WELLBORE FROM SURFACE TO TOTAL DEPTH.

Perforated Intervals, Fracturing, or Stimulating:

Perforated 22 intervals from 12,605' to 6,756'. Performed 22 individual stages of slick water stimulation using 7,756,356 gals fresh water, Sand - 882,014 lbs 100 Mesh and 8,055,536 lbs 40/70. AvBDP = 6,401 psi, AvTP = 6,970 psi, AvMTP = 9,120 psi, AvInjRate = 82.3 bpm, and AvSIP = 4,415 psi.

See Attachment for FracFocus information.

Plug Back Details Including Plug Type and Depth(s): N/A

Formations Encountered: Surface:	Top Depth	/	Bottom Depth
-------------------------------------	-----------	---	--------------

See attached sheet for formations encountered and their depths.

103-02772

BOWYERS #6H
 API 47-103-02772
 Stone Energy Corporation

	Horizontal		*	Bottom (ft	
	Top (ft TVD)	Top (ft MD)		TVD)	MD)
Sandstone & Shale	Surface		*	828	FW @ 90'
Pittsburgh Coal	828		*	832	
Sandstone & Shale	832		*	1733	SW - None Reported
Little Lime	1733		*	1768	
Big Lime	1768		*	1868	
Big Injun	1868		*	2062	
Sandstone & Shale	2062		*	2435	
Berea Sandstone	2435		*	2475	
Shale	2475		*	2665	
Gordon	2665		*	2725	
Undiff Devonian Shale	2275		*	5710	5735
Rhinestreet	5710	5735	~	6060	6106
Cashaqua	6060	6106	~	6189	6212
Middlesex	6189	6212	~	6212	6316
West River	6212	6316	~	6278	6432
Geneseo	6278	6432	~	6301	6482
Tully Limestone	6301	6482	~	6342	6589
Marcellus	6342	6589	~	6444	12722

TD

* From Pilot Hole Log and Driller's Log

~ From MWD Gamma Log

Hydraulic Fracturing Fluid Product Component Information Disclosure

103.02772

Fracture Date:	7/12/2013
State:	West Virginia
County/Parish:	Wetzel County
API Number:	
Operator Name:	Stone
Well Name and Number:	Bowyers 6H
Longitude:	
Latitude:	
Long/Lat Projection:	
Production Type:	
True Vertical Depth (TVD):	0
Total Water Volume (gal)*:	7756477

Hydraulic Fracturing Fluid Composition

Trade Name	Supplier	Purpose	Ingredients	Chemical Abstract Service Number (CAS #)	Maximum Ingredient Concentration in Additive (% by mass)**	Maximum Ingredient Concentration in HF Fluid (% by mass)**	Comments
15% HCl, Slickwater, WF115	Schlumberger	Corrosion Inhibitor, Bactericide (Myacide GA25), Scale Inhibitor, AntiFoam Agent, Surfactant, Acid, Breaker, Gelling Agent, Friction Reducer, Iron Control Agent, Clay Control Agent, Fluid Loss Additive, Propping	Water (Including Mix Water Supplied by Client)*	NA		87.68234%	
			Crystalline silica	14808-60-7	98.40813%	12.12158%	
			Hydrogen chloride	7647-01-0	0.69562%	0.08568%	
			Guar gum	9000-30-0	0.43075%	0.05306%	
			Acrylamide, 2-acrylamido-2-methylpropanesulfonic acid, sodium salt polymer	38193-60-1	0.08412%	0.01036%	
			Ammonium sulfate	7783-20-2	0.07951%	0.00979%	
			Polyethylene glycol monobutyl ether	31726-34-8	0.06290%	0.00775%	
			Glutaraldehyde	111-30-8	0.05845%	0.00720%	
			Sodium chloride	7647-14-5	0.03959%	0.00488%	
			Magnesium chloride	7786-30-3	0.03712%	0.00457%	
			Sodium sulfate	7757-82-6	0.03436%	0.00423%	
			Diammonium peroxidesulfate	7727-54-0	0.01875%	0.00231%	
			Polymer of 2-acrylamido-2-methylpropanesulfonic acid sodium salt and methyl acrylate	136793-29-8	0.00901%	0.00111%	
			Urea	57-13-6	0.00554%	0.00068%	
			Calcium chloride	10043-52-4	0.00520%	0.00064%	
			Sodium orthophosphate	7601-54-9	0.00319%	0.00039%	
			Dicoco dimethyl quaternary ammonium chloride	61789-77-3	0.00276%	0.00034%	
			Polypropylene glycol	25322-69-4	0.00275%	0.00034%	
			Sodium erythorbate	6381-77-7	0.00251%	0.00031%	
			Methanol	67-56-1	0.00199%	0.00025%	
			Non-crystalline silica	7631-86-9	0.00198%	0.00024%	
			Fatty acids, tall-oil	61790-12-3	0.00146%	0.00018%	
			Thiourea, polymer with formaldehyde and 1-propanethanone	68527-49-1	0.00120%	0.00015%	
			Potassium chloride	7447-40-7	0.00099%	0.00012%	
			Ethane-1,2-diol	107-21-1	0.00091%	0.00011%	
			Alcohols, C14-15, ahydroxylated (TEO)	68951-67-7	0.00056%	0.00007%	
			Propan-2-ol	67-63-0	0.00055%	0.00007%	
			Prop-2-yn-1-ol	107-19-7	0.00037%	0.00005%	
			Alkenes, C>10 a-	64743-02-8	0.00025%	0.00003%	
			Tetrasodium ethylenediaminetetraacetate	64-02-8	0.00017%	0.00002%	
			Potassium hydroxide	1310-58-3	0.00013%	0.00002%	
			Dimethyl siloxanes and silicones	63148-62-9	0.00008%	0.00001%	
			Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	0.00001%	< 0.00001%	
			Octamethylcyclotetrasiloxane	556-67-2	0.00001%	< 0.00001%	
			Sodium hydroxide	1310-73-2	0.00001%	< 0.00001%	
			Decamethyl cyclopentasiloxane	541-02-6	0.00001%	< 0.00001%	
			Dodecamethylcyclohexasiloxane	540-97-6	< 0.00001%	< 0.00001%	

† Proprietary Technology

* Total Water Volume sources may include fresh water, produced water, and/or recycled water

** Information is based on the maximum potential for concentration and thus the total may be over 100%

Report ID: RPT-16803 (Generated on 7/18/2013 4:32 PM)

All component information listed was obtained from the supplier's Material Safety Data Sheets (MSDS). As such, the Operator is not responsible for inaccurate and/or incomplete information. Any questions regarding the content of the MSDS should be directed to the supplier who provided it. The Occupational Safety and Health Administration's (OSHA) regulations govern the criteria for the disclosure of this information. Please note that Federal Law protects "proprietary", "trade secret", and "confidential business information" and the criteria for how this information is reported on an MSDS is subject to 29 CFR 1910.1200(i) and Appendix