

39° 40' 00"

Latitude

Longitude

80° 25' 00"

+
2.76s
1.72w

Topo Location

7.5' Loc. _____ 15' Loc. _____
(calc.) _____

Company Manufact Lt + Rt

Farm TJ Higgin botham #1907

15' Quad _____
(sec.)

7.5' Quad Hundred

District Church

WELL LOCATION PLAT

County 103 **Permit** 30017

Church District, Wetzel County, W. Va.

By The Manufacturers Light & Heat Co., 800 Union Trust Bldg.,

Pittsburgh, Pa.

Abandoned under permit Wey-17.

On 57 acres, surface owned by T. J. Higginbotham, R. D. 1, Glover Gap,
W. Va., and minerals by The Manufacturers Light & Heat Co.,

800 Union Trust Bldg., Pittsburgh, Pa.

Drilled June 11, 1916 (to 2630'). Gas well in Big Injun Sand.

Drilled deeper (dry on deepening) except for show of oil).

Abandonment reported to Dept. of Mines April 10, 1930.

Record to ROT from Mrs. Griffith Sept. 10, 1938.

	Top.	Bottom.	Thickness.
Mapletown (Sewickley) Coal	1170	- 1175	5
Pittsburgh Coal	1262	- 1269	7
Little Dunkard Sand	1600	- 1610	10
Sand	1625	- 1635	10
Sand	1680	- 1713	33
Big Dunkard Sand	1765	- 1800	35
Gas Sand	1915	- 1950	35
Salt Sand (2 bailers water per hour)	2000	- 2125	125
Sand	2175	- 2200	25
Marion Sand (little gas at 2435-2460'; no gas when completed)	2420	- 2475	55
Big Lime	2475	- 2535	60
Big Injun Sand (gas at 2545'; at 2605'; test, 14/10ths water in 6 $\frac{3}{8}$ " casing) (water test 7/10ths mercury in 6 $\frac{3}{8}$ " casing)	2535	- 2630	95
Total depth		2630	
DRILLED DEEPER:			
Pittsburgh Coal	1262	- 1269	7
Big Injun Sand	2535	- 2750	215
Slate and lime	2750	- 3210	460
50-Ft. Sand	3210	- 3233	23
Slate	3233	- 3237	4
30-Ft. Sand	3237	- 3247	10
Slate	3247	- 3255	8
30-Ft. Sand	3255	- 3274	19
Slate and shells	3274	- 3319	45
Red rock	3319	- 3322	3
Gordon Strey Sand (break from 3340-45')	3322	- 3356	34
Slate	3356	- 3370	14
Gordon Sand	3370	- 3437	67
Slate-Shells	3437	- 3462	25
4th Sand (show of oil, 3471-3482')	3462	- 3492	30
Slate and shells	3492	- 3595	103
Total depth		3595	

(Dry and abandoning).