



ACCURACY BM - USGS - USE

New Location

Drill Deeper

Abandonment

I, the undersigned, hereby certify that this map is correct to the best of my knowledge and belief and shows all the information required by paragraph 6 of the rules and regulations of the oil and gas section of the mining laws of W. Va.

Robert P. Wheeler, P.E.

Company Barron Kidd Oil & Gas

Address 273 Melbourne Place
Northampton, Ohio

Farm W. G. Snodgrass Mrs

Tract _____ Acres 57 Lease No. _____

Well (Farm) No. 1 Serial No. _____

Elevation (Spirit Level) 1373.6

Quadrangle Mannington - NC

County Wetzel District Church

Engineer Robert P. Wheeler
Surveyor by J. Herbert Nixingbotham

Engineer's Registration No. 3582

File No. _____ Drawing No. _____

Date 6-15-66 Scale 1" = 200'

STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION
CHARLESTON

WELL LOCATION MAP
FILE NO. WET-1205-A

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.

Church District, Wetsel County, W. Va. (on plat 1205A)
 By The Pure Oil Co. (The Ohio Cities Gas Co.) 103-70280
 Contractor, I. Gillette. Price per foot, \$2.00. NOT LOCATED
 Well started Nov. 1, 1919; completed, Dec. 10, 1919. 71316?
 Oil well. Good for about 10 bbls. natural.
 Shot Dec. 16, 1919, with 40 qts.
 16" conductor; 10" casing, 312'; 8 1/2", 1711'; 6-5/8", 2457'.
 Only one pay found. Well drilled to 2500 ft., then filled
 up to 2478 ft. to shoot.
 Well deepened. Location report sent in 3-12-23.
 Well started (deepening) April 1, 1923; completed, June 30, 1923.
 1st 24 hrs. production, 1,000,000 cu. ft. gas. (Deepening).
 Record from E. Townley, Room 208, 35 E. Wacker Drive,
 Chicago, Ill., March 13, 1931.

	Top.	Bottom.
Mapletown (Sewickley) Coal	1202	- 1205
Pittsburgh Coal	1312	- 1318
Little Dunkard Sand	1705	- 1755
Big Dunkard Sand	1730	- 1830
Gas Sand	1885	- 1925
1st Salt Sand	1950	- 2050
2nd Salt Sand	2125	- 2175
3rd Salt Sand	2205	- 2305
Red rock	2380	- 2383
Maxton Sand (oil, 2467-2475')	2455	
Break	2478	- 2480
Total depth		2500

(Filled up to 2478' to shoot).

DRILLED DEEPER:

Big Lime	2480	- 2550
Big Injun Sand (gas, 2645') (gas pay, 2650-2655')	2550	
Total depth		2655'

Shooting record: Shot Dec. 24, 1919, by Young Torpedo Co.,
 with 40 qts.; 8' shell; 3' anchor; depth of well when
 shot, 2478'; depth top of shot, 2467'; results, good.
 Filled up to 2478 ft. and cemented.

April 17, 1924, run in 95 ft. 5-3/16" casing for liner on
 disk packer without rubber at 2541' bottom liner; top
 liner, 2446'.

Other record gives "approximate" dates of deepening as:
 started May 9, 1923, and completed June 9, 1923.